


COLDZ^oNE

MEDIUM PROFILE UNIT COOLER



Walk-Ins: Medium to Large Cooler and Freezer Applications

Air Defrost

18,200 to 99,000 BTUH

Electric Defrost

11,000 to 86,300 BTUH

Hot Gas Defrost

11,000 to 64,300 BTUH



FEATURES

Our Medium Profile Unit Coolers are the perfect evaporator solution for medium to large walk-in coolers and freezers. Designed with efficiency, performance and service in mind, the Medium Profile line truly stands out from the competition. The unit coolers were engineered to meet the Department of Energy's new AWEF* performance regulations and all feature energy-efficient rail-mount Dual Speed EC Motors. For maximum performance, all units are circuited for multiple refrigerants and feature optimized circuit patterns, enhanced surface coil tubing, and new high efficiency fan and venturi designs. The Medium Profile product line has several serviceability features including rail-mount motors, easily removable fan guards and modular fan panels, face mount defrost heaters, hinged drain pans, and shipping pallets designed to facilitate quicker installation.

SIZES

There are a wide array of sizes available with capacities ranging from 11,000 to 99,000 BTUH at a 10° TD. Models are available with air flow spanning a range of 2,090 to 9,580 CFM.

HOUSING

Each unit is constructed with a rust-free, heavy gauge, textured, aluminum housing which is light weight yet extremely durable. Models feature hinged one-piece drain pans to allow for convenient servicing and maintenance. Hanger holes are provided on all units for fast installation.

COIL

Seamless copper tubes are staggered and mechanically expanded into corrugated aluminum fins to assure maximum heat transfer. Die formed fin collars are provided for accurate fin spacing. Top panel is fastened directly to the tube sheets of the coil to provide high structural strength. Low Temp Electric Defrost and Hot Gas Defrost Models are available in both 6 FPI and 4 FPI. Medium Temp Electric Defrost and Air Defrost models are available in 6 FPI.

MOTORS

All models feature highly efficient Dual Speed Electronically Commutated (EC) motors which are compliant with California Title 24 regulations.

FANS & FAN GUARDS

Powerful heavy-duty aluminum fans are individually balanced to provide vibration free operation. Standard heavy-gauge wire fan guards are UL/cUL-approved epoxy coated for corrosion resistance. Air throw for Medium Profile Unit Coolers is 75 ft.

REFRIGERANTS

Medium Profile Unit Coolers are optimized for multiple refrigerants including R404A, R407A, R448A, R449A and R744 DX (CO₂). Please specify system refrigerant requirements when ordering. A separate compartment is provided for all refrigerant connections which allows ample room for internal mounting of expansion valves.

AIR DEFROST

Air Defrost models are designed for use in coolers at +35°F room temperature and warmer.

ELECTRIC DEFROST - MEDIUM TEMP

Medium Temperature Electric Defrost Models are designed for use in coolers between 10°F and 35°F room temperatures. Defrost heaters are mounted on the air intake side of the unit for optimal performance and easy maintenance. Heaters are installed inside the drain pan for fast, reliable drainage. Adjustable defrost termination, fan delay and heater safety controls are factory mounted for optimum performance of each control function.

ELECTRIC DEFROST - LOW TEMP

Low Temperature Electric Defrost Models are designed for use in freezers between +10°F and -30°F room temperatures. Defrost heaters are mounted on the air intake side of the unit for optimal performance and easy maintenance. Heaters are installed inside the drain pan for fast, reliable drainage. Adjustable defrost termination, fan delay and heater safety controls are factory mounted for optimum performance of each control function.

HOT GAS DEFROST

There are two types of Hot Gas Defrost models available: 3-pipe Hot Gas models and 2-pipe Hot Gas Reverse Cycle units. Hot Gas Defrost models are designed for use in coolers and freezers between +35°F and -30°F. Hot Gas Defrost 4 FPI models are designed for use in freezers between +32°F and -30°F. All units include adjustable defrost termination and fan delay controls which are factory mounted for optimum performance of each control function. Hot Gas Defrost models feature electric drain pan heaters making it possible to open the hinged drain pan for easy cleaning and servicing. Refer to the current Technical Bulletin for piping.

ELECTRICAL

Available in 115/1² (Air Defrost only) 208-230V/1², 208-230V/3², 460V/1, or 460V/3². A large compartment is supplied for all electrical components and is easily accessible by removing the end panel. All models are UL and cUL listed.

OPTIONAL FEATURES

- EcoNet® Enabled Controller³ (factory-installed) (not available on Hot Gas Evaporators)
- EcoNet® Command Center (loose)
- Thermostat - Mechanical or Electric (mounted or loose)
- Thermostatic Expansion Valve (mounted or loose)
- Adjustable Defrost Termination
- Electronic Expansion Valve (mounted or loose)
- Liquid Line Solenoid Valve (mounted or loose)
- Insulated Drain Pan
- Painted Cabinet (White or Black)
- Stainless Steel Cabinet
- Coated Coil (Bronz-Glow, or Electrofin®)
- Suction/Liquid Heat Exchanger (loose)

* AWEF (Annual Walk-in Energy Factor)

1. Single Compressor system without variable capacity.

2. Some limitations apply. For specific electrical offering, consult electrical data tables in this brochure.

3. EcoNet Control Package includes EEV, suction pressure transducer, suction and entering air coil temp. thermistors, local on-board two-row backlit LCD display and push-button adjustments. (Controller replaces TXV, liquid line solenoid valve, room thermostat, defrost termination and fan delay, and time clock.)

ECONET ENABLED UNIT COOLERS (OPTIONAL)

Developed in conjunction with Rheem Manufacturing specifically for walk-in coolers and freezers — it builds on the reliability and efficiency of Rheem's EcoNet technology

- Saves energy in refrigeration systems through precise superheat and space temperature control, fan cycling, and controlling how often the system goes into defrost based on compressor runtime
- Eliminates unnecessary defrosts
- Maximizes energy efficiency with less compressor runtime
- Reduces fan speed to 50% during off cycle for energy savings
- Can be used with a condensing unit in single and multiple evaporator installations as a group

Optional EcoNet Command Center with intuitive graphical interface controls up to 32 devices (including the Command Center) through one display, continuous communication between system components, and remote mount display allows for EcoNet Enabled Unit Coolers to be programmed, monitored and troubleshoot outside of space being cooled.



MODEL NOMENCLATURE

C	M	6	E	153	D	D	A
Brand	Style	Fins per Inch (FPI)	Defrost Type	BTUH in Thousands	Unit Voltage ¹	Motor Type	Vintage
C = Coldzone	M = Medium Profile	4 FPI 6 FPI	A = Air D = Medium Temp Electric Defrost E = Low Temp Electric Defrost H = Hot Gas 3 Pipe Electric Drain Pan G = Hot Gas Rev Electric Drain Pan	XXX	A =115/1/60 D =208-230/1/60 E =208-230/3/60 F =460/1/60 G =460/3/60	D = Dual Speed EC	A

APPLICATION RATING AND ELECTRICAL DATA

AIR DEFROST MODELS

Model No.		BTUH Capacity @ +25°F S.T. & 10°F TD		CFM	No. of Fans	Total Fan Motor AMPS		
		R404A/ R744 DX (CO ₂)	R407A/ R448A/R449A^			115V/1	208-230V/1	460V/1
6 FPI	CM6A182*DA	18,200	21,100	3,190	1	3.2	1.9	1.2
	CM6A220*DA	22,000	25,800	2,950	1	3.2	1.9	1.2
	CM6A276*DA	27,600	32,300	6,950	2	6.4	3.8	2.4
	CM6A370*DA	37,000	43,100	6,380	2	6.4	3.8	2.4
	CM6A442*DA	44,200	51,900	5,900	2	6.4	3.8	2.4
	CM6A549*DA	54,900	64,200	9,580	3	9.6	5.7	3.6
	CM6A658*DA	65,800	76,900	8,860	3	9.6	5.7	3.6
	CM6A730*DA	73,000	85,600	12,770	4	12.8	7.6	4.8
	CM6A875*DA	87,500	99,000	11,800	4	12.8	7.6	4.8

* Asterisk represents a variable character based on voltage ordered. See page 4 for nomenclature.

^R407A, R448A and R449A are rated at dew point temperature. Use R407A capacity ratings for R407C and R407F.

APPLICATION RATING & ELECTRICAL DATA

MEDIUM TEMPERATURE ELECTRIC DEFROST

Model No.		BTUH Capacity @ +25°F S.T. & 10°F TD		CFM	No. of Fans	Total Fan Motor AMPS Dual Speed EC [†] Motors Motor Voltage	
		404/744 DX	407/448/449			208-230V/1	460V/1
6 FPI	CM6D181*DA	18,200	21,100	3,190	1	1.9	1.2
	CM6D219*DA	22,000	25,800	2,950	1	1.9	1.2
	CM6D275*DA	27,600	32,300	6,950	2	3.8	2.4
	CM6D369*DA	37,000	43,100	6,380	2	3.8	2.4
	CM6D441*DA	44,200	51,900	5,900	2	3.8	2.4
	CM6D548*DA	54,900	64,200	9,580	3	5.7	3.6
	CM6D657*DA	65,800	76,900	8,860	3	5.7	3.6
	CM6D729*DA	72,900	85,300	12,770	4	7.6	4.8
	CM6D874*DA	87,400	98,800	11,800	4	7.6	4.8

Model No.		208-230V/1				Heater Amps	Heater Watts
		MCA		MOPD			
		Base Model	EcoNet Enabled¹	Base Model	EcoNet Enabled¹	208-230V/1	
6 FPI	CM6D181DDA	15.0	20.5	20	25	19.5	4,480
	CM6D219DDA	15.0	20.5	20	25	19.5	4,480
	CM6D275DDA	20	40.5	20	45	38.5	8,860
	CM6D369DDA	20	40.5	20	45	38.5	8,860
	CM6D441DDA	20	40.5	20	45	38.5	8,860

Model No.		208-230V/3				Heater Amps	Heater Watts
		MCA		MOPD			
		Base Model	EcoNet Enabled ¹	Base Model	EcoNet Enabled ¹	208-230V/3	
6 FPI	CM6D181EDA	15.0	15.0	20	25	11.2	4,480
	CM6D219EDA	15.0	15.0	20	25	11.2	4,480
	CM6D275EDA	15.0	23.2	20	25	22.2	8,860
	CM6D369EDA	15.0	23.2	20	25	22.2	8,860
	CM6D441EDA	15.0	23.2	20	25	22.2	8,860
	CM6D548EDA	15.0	35.5	20	40	33.5	13,340
	CM6D657EDA	15.0	35.5	20	40	33.5	13,340
	CM6D729EDA	15.0	45.7	20	50	44.7	17,920
	CM6D874EDA	15.0	45.7	20	50	44.7	17,920

[†] EcoNet Enabled Units are not powered by Condensing Unit so Defrost Heaters are incorporated into shown MCA/MOPD. Econet Enabled calculations include additional 1 AMP for control voltages.

[^] R407A, R448A and R449A are rated at dew point temperature. Use R407A capacity ratings for R407C and R407F.

[†] Dual Speed EC motors are compliant with California Title 24 regulations.

Models were designed in anticipation of the July 2020 Department of Energy Annual Walk-in Energy Factor (AWEF) regulations for evaporators for Walk-in Coolers and Freezers in boxes less than 3,000 sq. ft. See page 26 for AWEF compliance ratings

APPLICATION RATING & ELECTRICAL DATA

MEDIUM TEMPERATURE ELECTRIC DEFROST

Model No.		460V/1				Heater Amps	Heater Watts
		MCA		MOPD			
		Base Model	EcoNet Enabled ¹	Base Model	EcoNet Enabled ¹	460V/1	
6 FPI	CM6D181FDA	15.0	15.0	20	25	9.7	4,480
	CM6D219FDA	15.0	15.0	20	25	9.7	4,480
	CM6D275FDA	15.0	20.3	20	25	19.3	8,860
	CM6D369FDA	15.0	20.3	20	25	19.3	8,860
	CM6D441FDA	15.0	20.3	20	25	19.3	8,860
	CM6D548FDA	15.0	30.0	20	35	29.0	13,340
	CM6D657FDA	15.0	30.0	20	35	29.0	13,340
	CM6D729FDA	15.0	39.7	20	40	38.7	17,920
	CM6D874FDA	15.0	39.7	20	40	38.7	17,920

Model No.		460V/3				Heater Amps	Heater Watts
		MCA		MOPD			
		Base Model	EcoNet Enabled ¹	Base Model	EcoNet Enabled ¹	460V/1	
6 FPI	CM6D181GDA	15.0	15.0	20	20	5.6	4,480
	CM6D219GDA	15.0	15.0	20	20	5.6	4,480
	CM6D275GDA	15.0	15.0	20	20	11.1	8,860
	CM6D369GDA	15.0	15.0	20	20	11.1	8,860
	CM6D441GDA	15.0	15.0	20	20	11.1	8,860
	CM6D548GDA	15.0	17.7	20	20	16.7	13,340
	CM6D657GDA	15.0	17.7	20	20	16.7	13,340
	CM6D729GDA	15.0	23.3	20	25	22.3	17,920
	CM6D874GDA	15.0	23.3	20	25	22.3	17,920

¹ EcoNet Enabled Units are not powered by Condensing Unit so Defrost Heaters are incorporated into shown MCA/MOPD. Econet Enabled calculations include additional 1 AMP for control voltages.

[^] R407A, R448A and R449A are rated at dew point temperature. Use R407A capacity ratings for R407C and R407F.

Models were designed in anticipation of the July 2020 Department of Energy Annual Walk-in Energy Factor (AWEF) regulations for evaporators for Walk-in Coolers and Freezers in boxes less than 3,000 sq. ft. See page 26 for AWEF compliance ratings

APPLICATION RATING & ELECTRICAL DATA

LOW TEMPERATURE ELECTRIC DEFROST

Model No.		BTUH Capacity @ -20°F S.T. & 10°F TD ¹		CFM	No. of Fans	Total Fan Motor AMPS Dual Speed EC [†] Motors Motor Voltage	
		R404A/R744 DX (CO ₂)	R407A/R448A/ R449A [^]			208-230V/1	460V/1
6 FPI	CM6E153*DA	15,300	17,400	2,250	1	1.9	1.2
	CM6E184*DA	18,400	21,100	2,090	1	1.9	1.2
	CM6E311*DA	31,100	35,700	4,500	2	3.8	2.4
	CM6E374*DA	37,400	42,900	4,180	2	3.8	2.4
	CM6E469*DA	46,900	53,600	6,750	3	5.7	3.6
	CM6E564*DA	56,400	64,300	6,270	3	5.7	3.6
	CM6E624*DA	62,400	71,100	9,000	4	7.6	4.8
	CM6E750*DA	75,000	86,300	8,360	4	7.6	4.8
4 FPI	CM4E110*DA	11,000	12,400	2,350	1	1.9	1.2
	CM4E143*DA	14,300	16,200	2,210	1	1.9	1.2
	CM4E232*DA	23,200	26,100	4,690	2	3.8	2.4
	CM4E288*DA	28,800	32,700	4,420	2	3.8	2.4
	CM4E336*DA	33,600	38,300	7,040	3	5.7	3.6
	CM4E419*DA	41,900	47,600	6,640	3	5.7	3.6
	CM4E447*DA	44,700	50,800	9,000	4	7.6	4.8
	CM4E557*DA	55,700	64,100	8,360	4	7.6	4.8

Capacity Correction for Electric Defrost Evaporators

S.S.T. (Dew)	20°F	0°F	-10°F	-20°F	-30°F	-40°F
Multiply Capacity by:	1.15	1.075	1.0375	1	0.9625	0.925

¹ Capacity values adjusted using the Correction Table for Electric Defrost Evaporators.

[^] R407A, R448A and R449A are rated at dew point temperature. Use R407A capacity ratings for R407C and R407F.

[†] Dual Speed EC motors are compliant with California Title 24 regulations. Models were designed in anticipation of the July 2020 Department of Energy Annual Walk-in Energy Factor (AWEF) regulations for evaporators for Walk-in Coolers and Freezers in boxes less than 3,000 sq. ft. See page 26 for AWEF compliance ratings.

APPLICATION RATING & ELECTRICAL DATA

LOW TEMPERATURE ELECTRIC DEFROST

Model No.		208-230V/1				Heater Amps	Heater Watts
		MCA		MOPD			
		Base Model	EcoNet Enabled ¹	Base Model	EcoNet Enabled ¹	208-230V/1	
6 FPI	CM6E153DDA	15.0	20.5	20	25	19.5	4,480
	CM6E184DDA	15.0	20.5	20	25	19.5	4,480
	CM6E311DDA	15.0	40.5	20	45	38.5	8,860
	CM6E374DDA	15.0	40.5	20	45	38.5	8,860
4 FPI	CM4E110DDA	15.0	20.5	20	25	19.5	4,480
	CM4E143DDA	15.0	20.5	20	25	19.5	4,480
	CM4E232DDA	15.0	40.5	20	45	38.5	8,860
	CM4E288DDA	15.0	40.5	20	45	38.5	8,860

Model No.		208-230V/3				Heater Amps	Heater Watts
		MCA		MOPD			
		Base Model	EcoNet Enabled¹	Base Model	EcoNet Enabled¹	208-230V/3	
6 FPI	CM6E153EDA	15.0	15.0	20	25	11.2	4,480
	CM6E184EDA	15.0	15.0	20	25	11.2	4,480
	CM6E311EDA	15.0	23.2	20	25	22.2	8,860
	CM6E374EDA	15.0	23.2	20	25	22.2	8,860
	CM6E469EDA	15.0	35.5	20	40	35.5	13,340
	CM6E564EDA	15.0	35.5	20	40	35.5	13,340
	CM6E624EDA	15.0	45.7	20	50	44.7	17,920
	CM6E750EDA	15.0	45.7	20	50	44.7	17,920
4 FPI	CM4E110EDA	15.0	15.0	20	25	11.2	4,480
	CM4E143EDA	15.0	15.0	20	25	11.2	4,480
	CM4E232EDA	15.0	23.2	20	25	22.2	8,860
	CM4E288EDA	15.0	23.2	20	25	22.2	8,860
	CM4E336EDA	15.0	35.5	20	40	35.5	13,340
	CM4E419EDA	15.0	35.5	20	40	35.5	13,340
	CM4E447EDA	15.0	45.7	20	50	44.7	17,920
	CM4E557EDA	15.0	45.7	20	50	44.7	17,920

¹ EcoNet Enabled Units are not powered by Condensing Unit so Defrost Heaters are incorporated into shown MCA/MOPD. Econet Enabled calculations include additional 1 amp for control voltages.

APPLICATION RATING & ELECTRICAL DATA

LOW TEMPERATURE ELECTRIC DEFROST

Model No.		460V/1				Heater Amps	Heater Watts
		MCA		MOPD			
		Base Model	EcoNet Enabled ¹	Base Model	EcoNet Enabled ¹	460V/1	
6 FPI	CM6E153FDA	15.0	15.0	20	25	9.7	4,480
	CM6E184FDA	15.0	15.0	20	25	9.7	4,480
	CM6E311FDA	15.0	20.3	20	25	19.3	8,860
	CM6E374FDA	15.0	20.3	20	25	19.3	8,860
	CM6E469FDA	15.0	30.0	20	35	29.0	13,340
	CM6E564FDA	15.0	30.0	20	35	29.0	13,340
	CM6E624FDA	15.0	39.7	20	40	38.7	17,920
	CM6E750FDA	15.0	39.7	20	40	38.7	17,920
4 FPI	CM4E110FDA	15.0	15.0	20	25	9.7	4,480
	CM4E143FDA	15.0	15.0	20	25	9.7	4,480
	CM4E232FDA	15.0	20.3	20	25	19.3	8,860
	CM4E288FDA	15.0	20.3	20	25	19.3	8,860
	CM4E336FDA	15.0	30.0	20	35	29.0	13,340
	CM4E419FDA	15.0	30.0	20	35	29.0	13,340
	CM4E447FDA	15.0	39.7	20	40	38.7	17,920
	CM4E557FDA	15.0	39.7	20	40	38.7	17,920

¹ EcoNet Enabled Units are not powered by Condensing Unit so Defrost Heaters are incorporated into shown MCA/MOPD.

Econet Enabled calculations include additional 1 AMP for control voltages.

Models were designed in anticipation of the July 2020 Department of Energy Annual Walk-in Energy Factor (AWEF) regulations for evaporators for Walk-in Coolers and Freezers in boxes less than 3,000 sq. ft. See page 26 for AWEF compliance ratings

APPLICATION RATING & ELECTRICAL DATA

LOW TEMPERATURE ELECTRIC DEFROST

Model No.		460V/3				Heater Amps	Heater Watts
		MCA		MOPD			
		Base Model	EcoNet Enabled ¹	Base Model	EcoNet Enabled ¹	460V/3	
6 FPI	CM6E153GDA	15.0	15.0	20	20	5.6	4,480
	CM6E184GDA	15.0	15.0	20	20	5.6	4,480
	CM6E311GDA	15.0	15.0	20	20	11.1	8,860
	CM6E374GDA	15.0	15.0	20	20	11.1	8,860
	CM6E469GDA	15.0	17.7	20	20	16.7	13,340
	CM6E564GDA	15.0	17.7	20	20	16.7	13,340
	CM6E624GDA	15.0	23.3	20	25	22.3	17,920
	CM6E750GDA	15.0	23.3	20	25	22.3	17,920
4 FPI	CM4E110GDA	15.0	15.0	20	20	5.6	4,480
	CM4E143GDA	15.0	15.0	20	20	5.6	4,480
	CM4E232GDA	15.0	15.0	20	20	11.1	8,860
	CM4E288GDA	15.0	15.0	20	20	11.1	8,860
	CM4E336GDA	15.0	17.7	20	20	16.7	13,340
	CM4E419GDA	15.0	17.7	20	20	16.7	13,340
	CM4E447GDA	15.0	23.3	20	25	22.3	17,920
	CM4E557GDA	15.0	23.3	20	25	22.3	17,920

¹ EcoNet Enabled Units are not powered by Condensing Unit so Defrost Heaters are incorporated into shown MCA/MOPD.

Econet Enabled calculations include additional 1 AMP for control voltages.

Models were designed in anticipation of the July 2020 Department of Energy Annual Walk-in Energy Factor (AWEF) regulations for evaporators for Walk-in Coolers and Freezers in boxes less than 3,000 sq. ft. See page 26 for AWEF compliance ratings

APPLICATION RATING & ELECTRICAL DATA

HOT GAS 3-PIPE DEFROST

Hot Gas 3-Pipe Model No.*		BTUH Capacity @ -20°F S.T. & 10°F TD ¹		CFM	No. of Fans	Total Fan Motor AMPS Dual Speed EC [†] Motors Motor Voltage		MCA	MOPD
		R404A	R407A/ R448A/R449A [^]			208-230V/1	460V/1		
6 FPI	CM6H153*DA	15,300	17,400	2,250	1	1.9	1.2	15.0	20
	CM6H184*DA	18,400	21,100	2,090	1	1.9	1.2	15.0	20
	CM6H311*DA	31,100	35,700	4,500	2	3.8	2.4	15.0	20
	CM6H374*DA	37,400	42,900	4,180	2	3.8	2.4	15.0	20
	CM6H469*DA	46,900	53,600	6,750	3	5.7	3.6	15.0	20
	CM6H564*DA	56,400	64,300	6,270	3	5.7	3.6	15.0	20
4 FPI	CM4H110*DA	11,000	12,400	2,350	1	1.9	1.2	15.0	20
	CM4H143*DA	14,300	16,200	2,210	1	1.9	1.2	15.0	20
	CM4H232*DA	23,200	26,100	4,690	2	3.8	2.4	15.0	20
	CM4H288*DA	28,800	32,700	4,420	2	3.8	2.4	15.0	20
	CM4H336*DA	33,600	38,300	7,040	3	5.7	3.6	15.0	20
	CM4H419*DA	41,900	47,600	6,640	3	5.7	3.6	15.0	20

Hot Gas 3-Pipe Model No.*		Drain Pan Heater Amps		Drain Pan Heater Watts
		208-230V/1	460V/1	
6 FPI	CM6H153*DA	15,300	15,300	1,480
	CM6H184*DA	15,300	15,300	1,480
	CM6H311*DA	15,300	15,300	2,960
	CM6H374*DA	15,300	15,300	2,960
	CM6H469*DA	15,300	15,300	4,440
	CM6H564*DA	15,300	15,300	4,440
4 FPI	CM4H110*DA	15,300	15,300	1,480
	CM4H143*DA	15,300	15,300	1,480
	CM4H232*DA	15,300	15,300	2,960
	CM4H288*DA	15,300	15,300	2,960
	CM4H336*DA	15,300	15,300	4,440
	CM4H419*DA	15,300	15,300	4,440

HOT GAS 3-PIPE MODEL

The system uses 3 pipes — 1 for liquid line, 1 for suction line and 1 for hot gas. The hot gas is taken from the discharge line, between the compressor and the condenser, through a hot-gas solenoid valve to the distributor tee then through the coil.

Capacity Correction for Hot Gas Defrost Evaporators

S.S.T. (Dew)	20°F	0°F	-10°F	-20°F	-30°F	-40°F
Multiply Capacity by:	1.15	1.075	1.0375	1	0.9625	0.925

¹ Capacity values adjusted using the Correction Table for Hot Gas Defrost Evaporators

* Each asterisk represents a variable character based on voltage ordered. See page 4 for nomenclature.

* Hot Gas models include an electric drain pan.

[†] Dual Speed EC motors are compliant with California Title 24 regulations.

[^] R407A, R448A and R449A are rated at dew point temperature. Use R407A capacity ratings for R407C and R407F.

Models were designed in anticipation of the July 2020 Department of Energy Annual Walk-in Energy Factor (AWEF) regulations for evaporators for Walk-in Coolers and Freezers in boxes less than 3,000 sq. ft. See page 26 for AWEF compliance ratings.

APPLICATION RATING & ELECTRICAL DATA

HOT GAS REVERSE CYCLE

Hot Gas Reverse Cycle Model No.*		BTUH Capacity @ -20°F S.T. & 10°F TD [†]		CFM	No. of Fans	Total Fan Motor AMPS Dual Speed EC [‡] Motors Motor Voltage		MCA	MOPD
		R404A	R407A/ R448A/R449A [^]			208-230V/1	460V/1		
6 FPI	CM6G153*DA	15,300	17,400	2,250	1	1.9	1.2	15.0	20
	CM6G184*DA	18,400	21,100	2,090	1	1.9	1.2	15.0	20
	CM6G311*DA	31,100	35,700	4,500	2	3.8	2.4	15.0	20
	CM6G374*DA	37,400	42,900	4,180	2	3.8	2.4	15.0	20
	CM6G469*DA	46,900	53,600	6,750	3	5.7	3.6	15.0	20
	CM6G564*DA	56,400	64,300	6,270	3	5.7	3.6	15.0	20
4 FPI	CM4G110*DA	11,000	12,400	2,350	1	1.9	1.2	15.0	20
	CM4G143*DA	14,300	16,200	2,210	1	1.9	1.2	15.0	20
	CM4G232*DA	23,200	26,100	4,690	2	3.8	2.4	15.0	20
	CM4G288*DA	28,800	32,700	4,420	2	3.8	2.4	15.0	20
	CM4G336*DA	33,600	38,300	7,040	3	5.7	3.6	15.0	20
	CM4G419*DA	41,900	47,600	6,640	3	5.7	3.6	15.0	20

Hot Gas Reverse Cycle Model No.*		Drain Pan Heater Amps		Drain Pan Heater Watts
		208-230V/1	460V/1	
6 FPI	CM6G153*DA	6.4	3.2	1,480
	CM6G184*DA	6.4	3.2	1,480
	CM6G311*DA	12.9	6.4	2,960
	CM6G374*DA	12.9	6.4	2,960
	CM6G469*DA	19.3	9.7	4,440
	CM6G564*DA	19.3	9.7	4,440
4 FPI	CM4G110*DA	6.4	3.2	1,480
	CM4G143*DA	6.4	3.2	1,480
	CM4G232*DA	12.9	6.4	2,960
	CM4G288*DA	12.9	6.4	2,960
	CM4G336*DA	19.3	9.7	4,440
	CM4G419*DA	19.3	9.7	4,440

HOT GAS REVERSE CYCLE 2-PIPE MODEL

A changeover valve is located in the discharge suction line of the compressor, so that when defrost is required, the valve changes over from the normal refrigeration flow so that the discharged gas flows into the suction connection and bypasses TX valve.

Capacity Correction for Hot Gas Defrost Evaporators

S.S.T. (Dew)	20°F	0°F	-10°F	-20°F	-30°F	-40°F
Multiply Capacity by:	1.15	1.075	1.0375	1	0.9625	0.925

[†] Capacity values adjusted using the Correction Table for Hot Gas Defrost Evaporators

* Each asterisk represents a variable character based on voltage ordered. See page 4 for nomenclature.

* Hot Gas models include an electric drain pan.

[‡] Dual Speed EC motors are compliant with California Title 24 regulations.

[^] R407A, R448A and R449A are rated at dew point temperature. Use R407A capacity ratings for R407C and R407F.

Models were designed in anticipation of the July 2020 Department of Energy Annual Walk-in Energy Factor (AWEF) regulations for evaporators for Walk-in Coolers and Freezers in boxes less than 3,000 sq. ft. See page 26 for AWEF compliance ratings.

DISTRIBUTOR NOZZLES & EXPANSION VALVES

AIR DEFROST

Model No.		Part Numbers						No. of Circuits
		Nozzle @ Liq. Temp.		TXV^ @ Liq. Temp.		EEV @ Liq. Temp.		
		50°F	100°F	50°F	100°F	50°F	100°F	
6 FPI - R404A	CM6A182*DA	L-3/4	L-2	SBFSE-B-C	SBFSE-B-C	SER-B	SER-B	4
	CM6A220*DA	L-3/4	L-2-1/2	SBFSE-B-C	SBFSE-B-C	SER-B	SER-B	6
	CM6A276*DA	L-1	L-3	SBFSE-B-C	SBFSE-B-C	SER-B	SER-C	8
	CM6A370*DA	L-1-1/2	L-4	SBFSE-C-C	SBFSE-C-C	SER-C	SER-C	9
	CM6A442*DA	G-1-1/2	G-5	EBSSSE-6-C	EBSSSE-6-C	SER-C	SER-C	12
	CM6A549*DA	G-2	G-6	EBSSSE-6-C	EBSSSE-6-C	SER-C	SER-C	12
	CM6A658*DA	G-2-1/2	G-8	EBSSSE-6-C	EBSSSE-6-C	SER-C	SER-D	16
	CM6A730*DA	G-3	G-10	EBSSSE-6-C	EBSSSE-7.5-C	SER-C	SER-DS	18
	CM6A875*DA	F-3	G-12	EBSSSE-6-C	EBSSSE-10-C	SER-DS	SER-DS	24
6 FPI - R407A, R407C†	CM6A182*DA	L-3/4	L-2	SBFDE-B-C	SBFDE-B-C	SER-B	SER-B	4
	CM6A220*DA	L-3/4	L-2-1/2	SBFDE-B-C	SBFDE-B-C	SER-B	SER-B	6
	CM6A276*DA	L-1	L-3	SBFDE-B-C	SBFDE-B-C	SER-B	SER-C	8
	CM6A370*DA	L-1-1/2	L-4	SBFDE-C-C	SBFDE-C-C	SER-C	SER-C	9
	CM6A442*DA	G-1-1/2	G-5	SBFDE-C-C	SBFDE-C-C	SER-C	SER-C	12
	CM6A549*DA	G-2	G-6	EBSDSE-7-C	SBFDE-C-C	SER-C	SER-C	12
	CM6A658*DA	G-2-1/2	G-8	EBSDSE-7-C	EBSDSE-7-C	SER-C	SER-D	16
	CM6A730*DA	G-3	G-10	EBSDSE-7-C	EBSDSE-7-C	SER-C	SER-D	18
	CM6A875*DA	G-4	G-12	EBSDSE-7-C	EBSDSE-10-C	SER-D	SER-D	24
6 FPI - R448A, R449A†	CM6A182*DA	L-3/4	L-2	SBFDE-B-C	SBFDE-B-C	SER-B	SER-B	4
	CM6A220*DA	L-3/4	L-2-1/2	SBFDE-B-C	SBFDE-B-C	SER-B	SER-B	6
	CM6A276*DA	L-1	L-3	SBFDE-C-C	SBFDE-C-C	SER-B	SER-C	8
	CM6A370*DA	L-1-1/2	L-4	SBFDE-C-C	SBFDE-C-C	SER-C	SER-C	9
	CM6A442*DA	G-1-1/2	G-5	SBFDE-C-C	EBSDSE-7-C	SER-C	SER-C	12
	CM6A549*DA	G-2	G-6	EBSDSE-7-C	EBSDSE-7-C	SER-C	SER-C	12
	CM6A658*DA	G-2-1/2	G-8	EBSDSE-7-C	EBSDSE-7-C	SER-C	SER-D	16
	CM6A730*DA	G-3	G-10	EBSDSE-7-C	EBSDSE-7-C	SER-C	SER-D	18
	CM6A875*DA	G-4	G-12	EBSDSE-7-C	EBSDSE-10-C	SER-D	SER-D	24

The distributor lines are 3/16" tube & 21" long.

* Each asterisk represents a variable character based on voltage ordered. See page 4 for nomenclature.

[^] TXV selections are based on +25°F suction temp., 8°F to 12°F evaporator TD. Contact factory for operating conditions outside of this range.

[†] SBFDE expansion valves are compatible with R407A, R448A and R449A/B. For other valves, follow manufacturers selection guidelines.

Base models (no factory-mounted components) include nozzles sized for 100°F liquid shipped loose.

DISTRIBUTOR NOZZLES & EXPANSION VALVES

MEDIUM TEMPERATURE ELECTRIC DEFROST

Model No.		Part Numbers						No. of Circuits
		Nozzle @ Liq. Temp.		TXV @ Liq. Temp.		EEV @ Liq. Temp.		
		50°F	105°F	50°F	105°F	50°F	105°F	
6 FPI - R404A	CM6D181*DA	L-3/4	L-2	SBFSE-B-C	SBFSE-B-C	SER-B	SER-B	4
	CM6D219*DA	L-3/4	L-2-1/2	SBFSE-B-C	SBFSE-B-C	SER-B	SER-B	6
	CM6D275*DA	L-1	L-3	SBFSE-B-C	SBFSE-C-C	SER-B	SER-C	8
	CM6D369*DA	L-1-1/2	L-4	SBFSE-C-C	SBFSE-C-C	SER-C	SER-C	9
	CM6D441*DA	G-1-1/2	G-5	EBSSSE-6-C	EBSSSE-6-C	SER-C	SER-C	12
	CM6D548*DA	G-2	G-6	EBSSSE-6-C	EBSSSE-6-C	SER-C	SER-C	12
	CM6D657*DA	G-2-1/2	G-8	EBSSSE-6-C	EBSSSE-6-C	SER-C	SER-D	16
	CM6D729*DA	G-3	G-10	EBSSSE-6-C	EBSSSE-7.5-C	SER-C	SER-DS	18
	CM6D874*DA	G-3	G-12	EBSSSE-6-C	EBSSSE-10-C	SER-DS	SER-DS	24
6 FPI -R407A, R407C†	CM6D181*DA	L-3/4	L-2	SBFDE-B-C	SBFDE-B-C	SER-B	SER-B	4
	CM6D219*DA	L-3/4	L-2-1/2	SBFDE-B-C	SBFDE-B-C	SER-B	SER-B	6
	CM6D275*DA	L-1	L-3	SBFDE-B-C	SBFDE-B-C	SER-B	SER-C	8
	CM6D369*DA	L-1-1/2	L-4	SBFDE-C-C	SBFDE-C-C	SER-C	SER-C	9
	CM6D441*DA	G-1-1/2	G-5	SBFDE-C-C	SBFDE-C-C	SER-C	SER-C	12
	CM6D548*DA	G-2	G-6	EBSDE-7-C	SBFDE-C-C	SER-C	SER-C	12
	CM6D657*DA	G-2-1/2	G-8	EBSDE-7-C	EBSDE-7-C	SER-C	SER-D	16
	CM6D729*DA	G-3	G-10	EBSDE-7-C	EBSDE-7-C	SER-C	SER-D	18
	CM6D874*DA	G-4	G-12	EBSDE-7-C	EBSDE-10-C	SER-D	SER-D	24
6 FPI - R448A, R449A†	CM6D181*DA	L-3/4	L-2	SBFDE-B-C	SBFDE-B-C	SER-B	SER-B	4
	CM6D219*DA	L-3/4	L-2-1/2	SBFDE-B-C	SBFDE-B-C	SER-B	SER-B	6
	CM6D275*DA	L-1	L-3	SBFDE-C-C	SBFDE-C-C	SER-B	SER-C	8
	CM6D369*DA	L-1-1/2	L-4	SBFDE-C-C	SBFDE-C-C	SER-C	SER-C	9
	CM6D441*DA	G-1-1/2	G-5	SBFDE-C-C	EBSDE-7-C	SER-C	SER-C	12
	CM6D548*DA	G-2	G-6	EBSDE-7-C	EBSDE-7-C	SER-C	SER-C	12
	CM6D657*DA	G-2-1/2	G-8	EBSDE-7-C	EBSDE-7-C	SER-C	SER-D	16
	CM6D729*DA	F-3	G-10	EBSDE-7-C	EBSDE-7-C	SER-C	SER-D	18
	CM6D874*DA	G-4	F-12	EBSDE-7-C	EBSDE-10-C	SER-D	SER-D	24

The distributor lines are 3/16" tube & 21" long.

* Each asterisk represents a variable character based on voltage ordered. See page 4 for nomenclature.

^ TXV selections are based on +25°F suction temp., 8°F to 12°F evaporator TD. Contact factory for operating conditions outside of this range.

† SBFDE expansion valves are compatible with R407A, R448A and R449A/B. For other valves, follow manufacturers selection guidelines.

Base models (no factory-mounted components) include nozzles sized for 100°F liquid shipped loose.

DISTRIBUTOR NOZZLES AND EXPANSION VALVES

LOW TEMPERATURE ELECTRIC DEFROST

Model No.		Part Numbers						No. of Circuits
		Nozzle @ Liq. Temp.		TXV^ @ Liq. Temp.		EEV @ Liq. Temp.		
		50°F	100°F	50°F	100°F	50°F	100°F	
6 FPI - R404A	CM6E153*DA	L-1-1/2	L-2-1/2	SBFSE-B-Z	SBFSE-B-Z	SER-B	SER-B	6
	CM6E184*DA	L-1-1/2	L-3	SBFSE-B-Z	SBFSE-C-Z	SER-B	SER-B	8
	CM6E311*DA	G-2-1/2	G-5	SBFSE-C-Z	EBSSSE-6-Z	SER-B	SER-C	12
	CM6E374*DA	G-3	G-6	EBSSSE-6-Z	EBSSSE-6-Z	SER-C	SER-C	16
	CM6E469*DA	G-4	G-10	EBSSSE-6-Z	EBSSSE-7-1/2-Z	SER-C	SER-C	18
	CM6E564*DA	G-5	G-12	EBSSSE-7-1/2-Z	EBSSSE-10-Z	SER-C	SER-C	24
	CM6E624*DA	5	15	EBSSSE-7.5-Z	EBSSSE-10-Z	SER-C	SER-DS	18
	CM6E750*DA	6	17	EBSSSE-10-Z	EBSSSE-13-Z	SER-C	SER-DS	24
6 FPI - R407A/ R407C†	CM6E153*DA	L-1-1/2	L-2-1/2	SBFDE-B-Z	SBFDE-B-Z	SER-A	SER-B	6
	CM6E184*DA	L-1-1/2	L-3	SBFDE-B-Z	SBFDE-B-Z	SER-B	SER-B	8
	CM6E311*DA	G-2-1/2	G-5	SBFDE-C-Z	SBFDE-C-Z	SER-B	SER-C	12
	CM6E374*DA	G-3	G-6	SBFDE-C-Z	EBSD-7-Z	SER-C	SER-C	16
	CM6E469*DA	G-4	G-10	EBSD-7-Z	EBSD-7-Z	SER-C	SER-C	18
	CM6E564*DA	G-5	G-12	EBSD-7-Z	EBSD-10-Z	SER-C	SER-C	24
	CM6E624*DA	G-5	G-15	EBSD-10-Z	EBSD-12-Z	SER-C	SER-C	18
	CM6E750*DA	G-6	G-17	EBSD-10-Z	EBS-12-Z	SER-C	SER-D	24
6 FPI - R448A, R449A†	CM6E153*DA	L-1-1/2	L-2-1/2	SBFDE-B-Z	SBFDE-B-Z	SER-A	SER-B	6
	CM6E184*DA	L-1-1/2	L-3	SBFDE-B-Z	SBFDE-B-Z	SER-B	SER-B	8
	CM6E311*DA	G-2-1/2	G-5	SBFDE-C-Z	SBFDE-C-Z	SER-B	SER-C	12
	CM6E374*DA	G-3	G-6	EBSD-7-Z	EBSD-7-Z	SER-C	SER-C	16
	CM6E469*DA	G-4	G-10	EBSD-7-Z	EBSD-7-Z	SER-C	SER-C	18
	CM6E564*DA	G-5	G-12	EBSD-10-Z	EBSD-10-Z	SER-C	SER-C	24
	CM6E624*DA	G-5	G-15	EBSD-10-Z	EBSD-12-Z	SER-C	SER-C	18
	CM6E750*DA	G-6	G-17	EBSD-10-Z	EBS-12-Z	SER-C	SER-D	24

The distributor lines are 3/16" tube & 21" long.

* Each asterisk represents a variable character based on voltage ordered. See page 4 for nomenclature.

[^] TXV selections are based on -20°F suction temp., 8°F to 12°F evaporator TD. Contact factory for operating conditions outside of this range.

† SBFDE expansion valves are compatible with R407A, R448A and R449A/B. For other valves, follow manufacturers selection guidelines.

Base models (no factory-mounted components) include nozzles sized for 100°F liquid shipped loose.

DISTRIBUTOR NOZZLES AND EXPANSION VALVES

LOW TEMPERATURE ELECTRIC DEFROST

Model No.		Part Numbers						No. of Circuits
		Nozzle @ Liq. Temp.		TXV^ @ Liq. Temp.		EEV @ Liq. Temp.		
		50°F	100°F	50°F	100°F	50°F	100°F	
4 FPI - R404A	CM4E110*DA	L-1	L-2	SBFSE-A-Z	SBFSE-A-Z	SER-A	SER-A	4
	CM4E143*DA	L-1-1/2	L-2-1/2	SBFSE-A-Z	SBFSE-B-Z	SER-A	SER-B	6
	CM4E232*DA	L-2	L-4	SBFSE-B-Z	SBFSE-C-Z	SER-B	SER-B	9
	CM4E288*DA	G-2-1/2	G-5	SBFSE-C-Z	EBSSSE-6-Z	SER-B	SER-C	12
	CM4E336*DA	G-3	G-6	SBFSE-C-Z	EBSSSE-6-Z	SER-C	SER-C	12
	CM4E419*DA	G-4	G-8	EBSSE-6-Z	EBSSE-6-Z	SER-C	SER-C	16
	CM4E447*DA	4	10	EBSSE-6-Z	EBSSE-7.5-Z	SER-C	SER-C	18
	CM4E557*DA	5	12	EBSSE-6-Z	EBSSE-10-Z	SER-C	SER-DS	24
4 FPI - R407A, R407C†	CM4E110*DA	L-1	L-2	SBFDE-A-Z	SBFDE-A-Z	SER-A	SER-A	4
	CM4E143*DA	L-1-1/2	L-2-1/2	SBFDE-B-Z	SBFDE-B-Z	SER-A	SER-B	6
	CM4E232*DA	L-2	L-4	SBFDE-C-Z	SBFDE-C-Z	SER-B	SER-B	9
	CM4E288*DA	G-2-1/2	G-5	SBFDE-C-Z	SBFDE-C-Z	SER-B	SER-C	12
	CM4E336*DA	G-3	G-6	SBFDE-C-Z	SBFDE-C-Z	SER-B	SER-C	12
	CM4E419*DA	G-4	G-8	EBSDE-7-Z	EBSDE-7-Z	SER-C	SER-C	16
	CM4E447*DA	G-4	G-10	EBSDE-7-Z	EBSDE-7-Z	SER-C	SER-C	18
	CM4E557*DA	G-5	G-12	EBSDE-7-Z	EBSDE-10-Z	SER-C	SER-C	24
4 FPI - R448A, R449A†	CM4E110*DA	L-1	L-2	SBFDE-A-Z	SBFDE-A-Z	SER-A	SER-A	4
	CM4E143*DA	L-1-1/2	L-2-1/2	SBFDE-A-Z	SBFDE-A-Z	SER-A	SER-B	6
	CM4E232*DA	L-2	L-4	SBFDE-B-Z	SBFDE-C-Z	SER-B	SER-B	9
	CM4E288*DA	G-2-1/2	G-5	SBFDE-C-Z	SBFDE-C-Z	SER-B	SER-C	12
	CM4E336*DA	G-3	G-6	SBFDE-C-Z	EBSDE-7-Z	SER-B	SER-C	12
	CM4E419*DA	G-4	G-8	EBSDE-7-Z	EBSDE-7-Z	SER-C	SER-C	16
	CM4E447*DA	G-4	G-10	EBSDE-7-Z	EBSDE-7-Z	SER-C	SER-C	18
	CM4E557*DA	G-5	G-12	EBSDE-7-Z	EBSDE-10-Z	SER-C	SER-C	24

The distributor lines are 3/16" tube & 21" long.

* Each asterisk represents a variable character based on voltage ordered. See page 4 for nomenclature.

[^] TXV selections are based on -20°F suction temp., 8°F to 12°F evaporator TD. Contact factory for operating conditions outside of this range.

[†] SBFDE expansion valves are compatible with R407A, R448A and R449A/B. For other valves, follow manufacturers selection guidelines.

Base models (no factory-mounted components) include nozzles sized for 100°F liquid shipped loose.

DISTRIBUTOR NOZZLES AND EXPANSION VALVES

HOT GAS DEFROST

Model No.		Part Numbers						No. of Circuits
		Nozzle @ Liq. Temp.		TXV^ @ Liq. Temp.		EEV @ Liq. Temp.		
		50°F	105°F	50°F	105°F	50°F	105°F	
6 FPI - R404A	CM6*153*DA	L-1-1/2	L-2-1/2	SBFSE-B-Z	SBFSE-B-Z	SER-B	SER-B	6
	CM6*184*DA	G-1-1/2	G-3	SBFSE-B-Z	SBFSE-C-Z	SER-B	SER-B	8
	CM6*311*DA	G-2-1/2	G-5	SBFSE-C-Z	EBSSSE-6-Z	SER-B	SER-C	12
	CM6*374*DA	G-3	G-6	EBSSSE-6-Z	EBSSSE-6-Z	SER-C	SER-C	16
	CM6*469*DA	G-4	G-10	EBSSSE-6-Z	EBSSSE-7-1/2-Z	SER-C	SER-C	18
	CM6*564*DA	G-5	G-12	EBSSSE-7-1/2-Z	EBSSSE-10-Z	SER-C	SER-C	24
6 FPI - R407A, R407C	CM6*153*DA	L-1-1/2	L-2-1/2	SBFDE-B-Z	SBFDE-B-Z	SER-A	SER-B	6
	CM6*184*DA	G-1-1/2	G-3	SBFDE-B-Z	SBFDE-B-Z	SER-B	SER-B	8
	CM6*311*DA	G-2-1/2	G-5	SBFDE-C-Z	SBFDE-C-Z	SER-B	SER-C	12
	CM6*374*DA	G-3	G-6	SBFDE-C-Z	EBSD-7-Z	SER-C	SER-C	16
	CM6*469*DA	G-4	G-10	EBSD-7-Z	EBSD-7-Z	SER-C	SER-C	18
	CM6*564*DA	G-5	G-12	EBSD-7-Z	EBSD-10-Z	SER-C	SER-C	24
6 FPI - R448A/ R449A†	CM6*153*DA	L-1-1/2	L-2-1/2	SBFDE-B-Z	SBFDE-B-Z	SER-A	SER-A	6
	CM6*184*DA	G-1-1/2	G-3	SBFDE-B-Z	SBFDE-B-Z	SER-B	SER-B	8
	CM6*311*DA	G-2-1/2	G-5	SBFDE-C-Z	SBFDE-C-Z	SER-B	SER-B	12
	CM6*374*DA	G-3	G-6	EBSD-7-Z	EBSD-7-Z	SER-C	SER-C	16
	CM6*469*DA	G-4	G-10	EBSD-7-Z	EBSD-7-Z	SER-C	SER-C	18
	CM6*564*DA	G-5	G-12	EBSD-10-Z	EBSD-10-Z	SER-C	SER-C	24

The distributor lines are 3/16" tube & 21" long.

* Each asterisk represents a variable character based on voltage ordered. See page 4 for nomenclature.

[^] TXV selections are based on -20°F suction temp., 8°F to 12°F evaporator TD. Contact factory for operating conditions outside of this range.

[†] SBFDE expansion valves are compatible with R407A, R448A and R449A/B. For other valves, follow manufacturers selection guidelines.

Base models (no factory-mounted components) include nozzles sized for 100°F liquid shipped loose.

DISTRIBUTOR NOZZLES AND EXPANSION VALVES

HOT GAS DEFROST

Model No.		Part Numbers						No. of Circuits
		Nozzle @ Liq. Temp.		TXV^ @ Liq. Temp.		EEV @ Liq. Temp.		
		50°F	105°F	50°F	105°F	50°F	105°F	
4 FPI - R404A	CM4*110*DA	L-1	L-2	SBFSE-A-Z	SBFSE-A-Z	SER-A	SER-A	4
	CM4*143*DA	L-1-1/2	L-2-1/2	SBFSE-A-Z	SBFSE-B-Z	SER-A	SER-B	6
	CM4*232*DA	G-2	G-4	SBFSE-B-Z	SBFSE-C-Z	SER-B	SER-B	9
	CM4*288*DA	G-2-1/2	G-5	SBFSE-C-Z	EBSSSE-6-Z	SER-B	SER-C	12
	CM4*336*DA	G-3	G-6	SBFSE-C-Z	EBSSSE-6-Z	SER-C	SER-C	12
	CM4*419*DA	G-4	G-8	EBSSSE-6-Z	EBSSSE-6-Z	SER-C	SER-C	16
4 FPI - R407A/ R407C†	CM4*110*DA	L-1	L-2	SBFDE-A-Z	SBFDE-A-Z	SER-A	SER-A	4
	CM4*143*DA	L-1-1/2	L-2-1/2	SBFDE-B-Z	SBFDE-B-Z	SER-A	SER-B	6
	CM4*232*DA	G-2	G-4	SBFDE-C-Z	SBFDE-C-Z	SER-B	SER-B	9
	CM4*288*DA	G-2-1/2	G-5	SBFDE-C-Z	SBFDE-C-Z	SER-B	SER-C	12
	CM4*336*DA	G-3	G-6	SBFDE-C-Z	SBFDE-C-Z	SER-B	SER-C	12
	CM4*419*DA	G-4	G-8	EBSDE-7-Z	EBSDE-7-Z	SER-C	SER-C	16
4 FPI - R448A R449A†	CM4*110*DA	L-1	L-2	SBFDE-A-Z	SBFDE-A-Z	SER-A	SER-A	4
	CM4*143*DA	L-1-1/2	L-2-1/2	SBFDE-A-Z	SBFDE-A-Z	SER-A	SER-A	6
	CM4*232*DA	G-2	G-4	SBFDE-B-Z	SBFDE-C-Z	SER-B	SER-B	9
	CM4*288*DA	G-2-1/2	G-5	SBFDE-C-Z	SBFDE-C-Z	SER-B	SER-B	12
	CM4*336*DA	G-3	G-6	SBFDE-C-Z	EBSDE-7-Z	SER-B	SER-B	12
	CM4*419*DA	G-4	G-8	EBSDE-7-Z	EBSDE-7-Z	SER-C	SER-C	16

The distributor lines are 3/16" tube & 21" long.

* Each asterisk represents a variable character based on voltage ordered. See page 4 for nomenclature.

[^] TXV selections are based on -20°F suction temp., 8°F to 12°F evaporator TD. Contact factory for operating conditions outside of this range.

[†] SBFDE expansion valves are compatible with R407A, R448A and R449A/B. For other valves, follow manufacturers selection guidelines.

Base models (no factory-mounted components) include nozzles sized for 100°F liquid shipped loose.

SPECIFICATIONS

AIR DEFROST MODELS

Model No.		Fan Diam. (In.)	Motor Data			Refrigerant Connections		No. of Hangers Slot Location	Fig.	Unit Dimensions (In.)			Approx. Unit Wt. (Lbs.)
			Motor Qty.	HP	RPM	Liquid Line [^]	Suction			L	W	H	
6 FPI	CM6A182*DA	24	1	1/3	850	3/8	7/8	4	1	47-1/2	21-5/16	33-7/8	120
	CM6A220*DA	24	1	1/3	850	3/8	7/8	4	1	47-1/2	21-5/16	33-7/8	120
	CM6A276*DA	24	2	1/3	850	1/2	1-1/8	6	2	80-1/2	21-5/16	33-7/8	220
	CM6A370*DA	24	2	1/3	850	1/2	1-1/8	6	2	80-1/2	21-5/16	33-7/8	220
	CM6A442*DA	24	2	1/3	850	5/8	1-1/8	6	2	80-1/2	21-5/16	33-7/8	220
	CM6A549*DA	24	3	1/3	850	5/8	1-3/8	8	3	113-9/16	21-5/16	33-7/8	316
	CM6A658*DA	24	3	1/3	850	5/8	1-3/8	8	3	113-9/16	21-5/16	33-7/8	316
	CM6A730*DA	24	4	1/3	850	7/8	1-5/8	10	4	146-9/16	21-5/16	33-7/8	416
	CM6A875*DA	24	4	1/3	850	7/8	1-5/8	10	4	146-9/16	21-5/16	33-7/8	416

SPECIFICATIONS // MEDIUM TEMPERATURE ELECTRIC DEFROST MODELS

Model No.		Fan Diam. (In.)	Motor Data			Refrigerant Connections		No. of Hangers Slot Location	Fig.	Unit Dimensions (In.)			Approx. Unit Wt. (Lbs.)
			Motor Qty	HP	RPM	Liquid Line [^]	Suction			L	W	H	
6 FPI	CM6D181*DA	24	1	1/3	850	3/8	7/8	4	1	47-1/2	21-5/16	33-7/8	120
	CM6D219*DA	24	1	1/3	850	3/8	7/8	4	1	47-1/2	21-5/16	33-7/8	120
	CM6D275*DA	24	2	1/3	850	1/2	1-1/8	6	2	80-1/2	21-5/16	33-7/8	220
	CM6D369*DA	24	2	1/3	850	1/2	1-1/8	6	2	80-1/2	21-5/16	33-7/8	220
	CM6D441*DA	24	2	1/3	850	5/8	1-1/8	6	2	80-1/2	21-5/16	33-7/8	220
	CM6D548*DA	24	3	1/3	850	5/8	1-3/8	8	3	113-9/16	21-5/16	33-7/8	316
	CM6D657*DA	24	3	1/3	850	5/8	1-3/8	8	3	113-9/16	21-5/16	33-7/8	316
	CM6D729*DA	24	4	1/3	850	7/8	1-5/8	10	4	146-9/16	21-5/16	33-7/8	416
	CM6D874*DA	24	4	1/3	850	7/8	1-5/8	10	4	146-9/16	21-5/16	33-7/8	416

* Each asterisk represents a variable character based on voltage ordered. See page 4 for nomenclature.

[^] For units with mounted TXV components. See Nozzle/TXV table for distributor connection size when TXV is field installed.

For dimensional distance between hanger slots, consult model's corresponding dimension drawing. Hanger slots are 3/8" deep x 1" wide.

Drain is 1-1/4" NPT for all models.

SPECIFICATIONS

LOW TEMPERATURE ELECTRIC DEFROST MODELS

Model No.		Fan Diam. (In.)	Motor Data			Refrigerant Connections		No. of Hanger Slot Loc.	Fig.	Unit Dimensions (In.)			App. Unit Wt. (Lbs.)
			Motor Qty.	HP	RPM	Liquid Line [^]	Suction			L	W	H	
6 FPI - RM*E/G/H	CM6E153EDA	24	1	1/3	850	3/8	1-1/8	4	1	47-1/2	21-5/16	33-7/8	120
	CM6E184EDA	24	1	1/3	850	3/8	1-1/8	4	1	47-1/2	21-5/16	33-7/8	120
	CM6E311EDA	24	2	1/3	850	1/2	1-5/8	6	2	80-1/2	21-5/16	33-7/8	220
	CM6E374EDA	24	2	1/3	850	5/8	1-5/8	6	2	80-1/2	21-5/16	33-7/8	220
	CM6E469EDA	24	3	1/3	850	5/8	2-1/8	8	3	113-9/16	21-5/16	33-7/8	320
	CM6E564EDA	24	3	1/3	850	5/8	2-1/8	8	3	113-9/16	21-5/16	33-7/8	320
	CM6E624EDA	24	4	1/3	850	7/8	2-1/8"	10	4	146-9/16	21-5/16	33-7/8	420
	CM6E750EDA	24	4	1/3	850	7/8	2-1/8"	10	4	146-9/16	21-5/16	33-7/8	420
4 FPI - RM*E/G/H	CM4E110*DA	24	1	1/3	850	3/8	1-1/8	4	1	47-1/2	21-5/16	33-7/8	120
	CM4E143*DA	24	1	1/3	850	3/8	1-1/8	4	1	47-1/2	21-5/16	33-7/8	120
	CM4E232*DA	24	2	1/3	850	1/2	1-3/8	6	2	80-1/2	21-5/16	33-7/8	220
	CM4E288*DA	24	2	1/3	850	1/2	1-3/8	6	2	80-1/2	21-5/16	33-7/8	220
	CM4E336*DA	24	3	1/3	850	1/2	1-5/8	8	3	113-9/16	21-5/16	33-7/8	320
	CM4E419*DA	24	3	1/3	850	5/8	1-5/8	8	3	113-9/16	21-5/16	33-7/8	320
	CM4E447*DA	24	4	1/3	850	5/8"	2-1/8"	10	4	146-9/16	21-5/16	33-7/8	420
	CM4E557*DA	24	4	1/3	850	5/8"	2-1/8"	10	4	146-9/16	21-5/16	33-7/8	420

* Each asterisk represents a variable character based on voltage ordered. See page 4 for nomenclature.

[^] For units with mounted TXV components. See Nozzle/TXV table for distributor connection size when TXV is field installed.


For dimensional distance between hanger slots, consult model's corresponding dimension drawing. Hanger slots are 3/8" deep x 1" wide.

Drain is 1-1/4" NPT for all models.


DIMENSIONAL DRAWINGS

Figure 1: Single Fan

Front View



Side View



Top View




FIGURE 1: SHIPPING INFORMATION


No. of Fans	Shipping Dimensions (Inches)			Shipping Weight (Lbs)
	L	W	H	
1	60	43-1/4	48-1/2	346

All mounting holes are 3/8" diameter.
All dimensions are in inches.


DIMENSIONAL DRAWINGS

Figure 2: Two Fan

Front View



Side View



Top View




FIGURE 2: SHIPPING INFORMATION

No. of Fans	Shipping Dimensions (Inches)			Shipping Weight (Lbs)
	L	W	H	
2	93	43-1/4	48-1/2	510

All mounting holes are 3/8" diameter.
All dimensions are in inches.

DIMENSIONAL DRAWINGS

Figure 3: Three Fan




FIGURE 3: SHIPPING INFORMATION


No. of Fans	Shipping Dimensions (Inches)			Shipping Weight (Lbs)
	L	W	H	
3	120	43-1/4	48-1/2	673

All mounting holes are 3/8" diameter.
All dimensions are in inches.


DIMENSIONAL DRAWINGS

Figure 4: Four Fan

Front View



Side View



Top View




FIGURE 4: SHIPPING INFORMATION

No. of Fans	Shipping Dimensions (Inches)			Shipping Weight (Lbs)
	L	W	H	
4	160	43-1/4	48-1/2	843

All mounting holes are 3/8" diameter.
All dimensions are in inches.

EVAPORATOR APPLICATION RATINGS

Multiple conditions combine to determine the application capacity of an evaporator. Walk-in space temperature, relative humidity, saturated suction temperature difference, and outdoor ambient temperature. All of the factors are considered when calculating an evaporator application rating. These ratings are considerably higher than the net capacity value used for DOE ratings (AWEF).

The AWEF of an evaporator is calculated using the dry coil capacity and the daily evaporator power consumption. Power consumption included fan and defrost power. Evaporator net capacity reported to the DOE database is dry coil capacity less the full power fan watts. DOE test conditions are at 10°F evaporator/SST temperature difference and less than 50% relative humidity and 96°F liquid temperature. These conditions create a uniform test method, but should not be used for equipment selection. The equipment selected would be too large for the application.

Published application ratings are a guideline for proper equipment selection. They account for true operating conditions experienced by equipment.

AWEF RATINGS // COOLER AND FREEZER MODELS

Department of Energy Annual Walk-In Energy Factor (AWEF) Ratings			
Base Model No.	Defrost Type	FPI	AWEF
COOLER MODELS¹			
CM6A182*DA	Air Defrost	6	9
CM6A220*DA	Air Defrost	6	9
CM6A276*DA	Air Defrost	6	9
CM6A370*DA	Air Defrost	6	9
CM6A442*DA	Air Defrost	6	9
CM6A549*DA	Air Defrost	6	9
CM6A658*DA	Air Defrost	6	9
CM6A730*DA	Air Defrost	6	9
CM6A875*DA	Air Defrost	6	9
CM6D181*DA	Med Temp Electric Defrost	6	9
CM6D219*DA	Med Temp Electric Defrost	6	9
CM6D275*DA	Med Temp Electric Defrost	6	9
CM6D369*DA	Med Temp Electric Defrost	6	9
CM6D441*DA	Med Temp Electric Defrost	6	9
CM6D548*DA	Med Temp Electric Defrost	6	9
CM6D657*DA	Med Temp Electric Defrost	6	9
CM6D729*DA	Med Temp Electric Defrost	6	9
CM6D874*DA	Med Temp Electric Defrost	6	9
CM6*153*DA	Med Temp Hot Gas Defrost	6	9
CM6*184*DA	Med Temp Hot Gas Defrost	6	9
CM6*311*DA	Med Temp Hot Gas Defrost	6	9
CM6*374*DA	Med Temp Hot Gas Defrost	6	9
CM6*469*DA	Med Temp Hot Gas Defrost	6	9
CM6*564*DA	Med Temp Hot Gas Defrost	6	9

Department of Energy Annual Walk-In Energy Factor (AWEF) Ratings			
Base Model No.	Defrost Type	FPI	AWEF
FREEZER MODELS²			
CM6E153*DA	Low Temp Electric Defrost	6	4.15
CM6E184*DA	Low Temp Electric Defrost	6	4.15
CM6E311*DA	Low Temp Electric Defrost	6	4.15
CM6E374*DA	Low Temp Electric Defrost	6	4.15
CM6E469*DA	Low Temp Electric Defrost	6	4.15
CM6E564*DA	Low Temp Electric Defrost	6	4.15
CM6E624*DA	Low Temp Electric Defrost	6	4.15
CM6E750*DA	Low Temp Electric Defrost	6	4.15
CM4E110*DA	Low Temp Electric Defrost	4	4.15
CM4E143*DA	Low Temp Electric Defrost	4	4.15
CM4E232*DA	Low Temp Electric Defrost	4	4.15
CM4E288*DA	Low Temp Electric Defrost	4	4.15
CM4E336*DA	Low Temp Electric Defrost	4	4.15
CM4E419*DA	Low Temp Electric Defrost	4	4.15
CM4E447*DA	Low Temp Electric Defrost	4	4.15
CM4E557*DA	Low Temp Electric Defrost	4	4.15
CM6*153*DA	Low Temp Hot Gas Defrost	6	4.15
CM6*184*DA	Low Temp Hot Gas Defrost	6	4.15
CM6*311*DA	Low Temp Hot Gas Defrost	6	4.15
CM6*374*DA	Low Temp Hot Gas Defrost	6	4.15
CM6*469*DA	Low Temp Hot Gas Defrost	6	4.15
CM6*564*DA	Low Temp Hot Gas Defrost	6	4.15
CM4*110*DA	Low Temp Hot Gas Defrost	4	4.15
CM4*143*DA	Low Temp Hot Gas Defrost	4	4.15
CM4*232*DA	Low Temp Hot Gas Defrost	4	4.15
CM4*288*DA	Low Temp Hot Gas Defrost	4	4.15
CM4*336*DA	Low Temp Hot Gas Defrost	4	4.15
CM4*419*DA	Low Temp Hot Gas Defrost	4	4.15

* Each asterisk represents a variable character based on voltage ordered. See page 4 for nomenclature.

¹ If the model has a numerical value in the table above, the following statement applies: "The evaporator is designed and certified for use in walk-in cooler applications."

² If the model has a numerical value in the table above, the following statement applies: "The evaporator is designed and certified for use in walk-in freezer applications."





COLDZ[®]NE

ENGINEERED FOR COOL.™

©2025 Heat Transfer Products Group

Published July 2025

CZ-RMX-A1-0725

coldzone.htpg.com

This information is the most current and accurate information available and is subject to change without notice. HTPG makes no warranty or guarantee of any kind, express or implied, regarding the information set forth herein, including without limitation warranty regarding its currency, accuracy or completeness or any warranty of merchantability or fitness for a particular purpose.

