

Heat Transfer Products Group, LLC A Division of Rheem Manufacturing 201Thomas French Drive Scottsboro, Alabama 35769

Date: 10 October 2024

SUBJECT: Wind Load Analysis of HTPG 1/2 to 31/2 HP Multi-Refrigerant Package Units

The following wind load analysis applies to all HTPG Multi-Refrigerant Package Units using the following nomenclature description:

Γ	R	Р	0	150	М	48	D	A
	1	2	3	4	5	6	7	8
The	The listings below are the positions for the model with a brief explanation.							

1	Branding: R Russell W \	Nitt K Kramer C ColdZone H HTPG ? Other brands may use single letter code or asterisk "*"
2	Product Type:	P Package Refrigeration System
3	Compressor Type:	H Hermetic O Scroll
4	Horsepower:	XXX Three numbers roughly equal to compressor horsepower times 100
5	Temperature Range:	L Low Temp M Medium Temp D Medium Temp Electric Defrost
6	Refrigerant Type:	44 R404A 48 R448A or R449A 4S compressor is rated for all refrigerants.
		4A A2L Refrigerants R454A/R454B/R454C/R455A/R32
8	Voltage/Phase/Frequency Code:	A 115/1/60 C 230/1/60 D 208-230/1/60
9	Revision Code:	Starting with letter A

The wind load analysis has determined these multi-refrigerant air cooled condensing units are in accordance with ASCE/SEI 7-22, Florida Building Code Eighth Edition (2023) for the following location:

Insta	Ilation locatio	n: Miami – Dao	le County, Florida	Installation Height: 60 feet					
	Roof Mounting Requirement								
			Max. Force at Each	Max Unit,					
	Cabinet Size	Number of Attachment Points	Hurricane Tension, Net Uplift Load (lbs)	Hurricane Shear, Horizontal Load (lbs)	Hurricane Net Overturning Moment (lbs.ft)				
	Small	6	480	169	2,018				
	Small w/ Roof Acc.	6	806	213	3,405				
	Large	6	483	169	2,384				
	Large w/ Roof Acc.	6	805	218	3,995				

Using a roof curb to install these condensing units requires a metal mounting surface with stand details to be provided by the selected mechanical contractor at the job site.

