




# A2L

## HEAVY DUTY UNIT COOLER



### Walk-Ins: Medium to Large Cooler and Freezer Applications

Air Defrost

38,000 to 263,000 BTUH

Electric Defrost

38,000 to 263,000 BTUH



### FEATURES

Heavy Duty Unit Coolers are the ideal evaporator solution for medium and large walk-in coolers and freezers. Designed with efficiency, performance and service in mind, the Heavy Duty Cooler line is optimized to cover Cold Storage applications in the most effective way. The Heavy Duty units were engineered to meet the Department of Energy's new AWEF performance regulations and feature energy-efficient rail-mount Dual Speed EC Motors.

All units are circuited for multiple refrigerants and feature optimized circuit patterns to maximize performance. Heavy Duty Unit Coolers have several enhanced service features including rail-mount motors, new high efficiency fan and venturi designs, enhanced surface coil tubing, easily removable fan guards and modular fan panels, face mount defrost heaters, hinged drain pans and shipping pallets designed to facilitate easy installation.

### SIZES

There are a wide array of sizes to match your specific application requirements ranging from 38,000 to 263,000 BTUH at a 10°TD. Models are available with air flow spanning a range of 5,920 to 23,000 CFM.

### HOUSING

Each unit is constructed with a rust-free, heavy gauge, textured, aluminum housing which is light weight yet extremely durable. Models feature hinged drain pans to allow for convenient servicing and maintenance. Pre-drilled hanger holes are provided on all units for fast installation.

### COIL

Seamless copper tubes are staggered and mechanically expanded into heavy gauge corrugated aluminum fins to assure maximum heat transfer. Die formed fin collars are provided for accurate fin spacing. Heavy gauge hangers are fastened directly to the tube sheet of the coil to provide high structural strength. Electric Defrost is available in both 6 FPI and 4 FPI.

### MOTORS

All models feature highly efficient Dual Speed Electronically Commutated (EC) motors which are compliant with California Title 24 regulations.

### FANS & FAN GUARDS

Powerful heavy-duty aluminum fans are individually balanced to provide vibration free operation. Standard heavy-gauge wire fan guards are UL/cUL-approved epoxy coated for corrosion resistance. Air throw for Heavy Duty Unit Coolers is up to 100 ft.

### REFRIGERANTS

Heavy Duty Unit Coolers are optimized for multiple refrigerants including R454A, R454C, and R455A. Please specify system refrigerant requirements when ordering. A separate compartment is provided for all refrigerant connections which allows ample room for internal mounting of expansion valves.

### ELECTRICAL

Available in 208-230V/1, 208-230V/3, 460/1, or 460/3. Heavy Duty Evaporators can also be operated on 220/1/50, 220/3/50, 380/1/50, and 380/3/50 power (Contact factory for details). A large compartment is supplied for all electrical components and is easily accessible by removing the end panel. All 60 Hz models are UL and cUL listed.

## AIR DEFROST

Air Defrost models are designed for use in coolers at +35°F and warmer.

## ELECTRIC DEFROST - MEDIUM TEMP

Heavy Duty Unit Coolers are designed for use in coolers between +11°F and +35°F room temperatures. Defrost heaters are mounted on the air intake side of the unit for optimal performance and easy maintenance. An additional Heater is installed inside the drain pan for fast, reliable drainage. Adjustable defrost termination, fan delay, and heater safety controls are factory mounted for optimum performance of each control function.

## ELECTRIC DEFROST - LOW TEMP

Low Temperature Electric Defrost Models are designed for use in freezers between +10°F and -30°F room temperatures. Defrost heaters are mounted on the air intake side of the unit for optimal performance and easy maintenance. An additional heater is installed inside the drain pan for fast, reliable drainage. Adjustable defrost termination, fan delay, and heater safety controls are factory-mounted for optimum performance of each control function.

## OPTIONAL FEATURES

- EcoNet® Enabled Controller<sup>3</sup> (factory-installed)
- EcoNet® Command Center (loose)
- Reverse Connections
- Thermostat - Mechanical or Electric (mounted or loose)
- Thermostatic Expansion Valve (mounted or loose)
- Electronic Expansion Valve (mounted or loose)
- Solenoid Shut Off Valve (loose)
- Check Shut Off Valve (loose)
- Insulated Drain Pan
- Painted Cabinet (White or Black)
- Stainless Steel Cabinet
- Coated Coil (Bronz-Glow, or Electrofin®)
- Suction/Liquid Heat Exchanger (loose)

\* AWEF (Annual Walk-in Energy Factor)

<sup>1</sup> Single Compressor system without variable capacity.

<sup>2</sup> Some limitations apply. For specific electrical offering, consult electrical data tables in this brochure.

<sup>3</sup> EcoNet® Control Package includes: EEV; suction pressure transducer, suction entering air coil temp. thermistors, local on-board two-row backlit LCD display and push-button adjustments. (Controller replaces TXV, liquid line solenoid valve, room thermostat, defrost termination and fan delay, and time clock.)

## ECONET® ENABLED UNIT COOLERS (OPTIONAL)

- Developed in conjunction with Rheem Manufacturing specifically for walk-in coolers and freezers — it builds on the reliability and efficiency of Rheem's EcoNet® technology
- Saves energy in refrigeration systems through precise superheat and space temperature control, fan cycling, and controlling how often the system goes into defrost based on compressor runtime
- Eliminates unnecessary defrosts
- Maximizes energy efficiency with less compressor runtime
- Reduces fan speed to 50% during off cycle for energy savings
- Can be used with a condensing unit in single and multiple evaporator installations as a group
- Optional EcoNet® Command Center with intuitive graphical interface controls up to 32 devices (including the Command Center) through one display, continuous communication between system components, and remote mount display allows for EcoNet® Enabled Unit Coolers to be programmed, monitored and troubleshot outside of space being cooled.



## MODEL NOMENCLATURE

| R           | A                 | H                                             | 6                   | E                                                                                            | 106               | E                                                                                 | D                  | A       |
|-------------|-------------------|-----------------------------------------------|---------------------|----------------------------------------------------------------------------------------------|-------------------|-----------------------------------------------------------------------------------|--------------------|---------|
| Brand       | Refrigerant Class | Style                                         | Fins per Inch (FPI) | Defrost Type                                                                                 | BTUH in Thousands | Unit Voltage                                                                      | Motor Type         | Vintage |
| R = Russell | A = A2L           | H = Heavy Duty<br><br>Y = Reverse Connections | 4 FPI<br>6 FPI      | A = Air Defrost<br><br>D = Medium Temp Electric Defrost<br><br>E = Low Temp Electric Defrost | XXX               | D = 208-230/1/60<br><br>E = 208-230//3/60<br><br>F = 460/1/60<br><br>G = 460/3/60 | D = Dual Speed ECM | A       |

EcoNet® approved refrigerants are: R454A, R454C, R455A

## APPLICATION RATING &amp; ELECTRICAL DATA

AIR DEFROST // 6 FPI

| Model No. |             | BTUH Capacity<br>@ +25°F SST & 10°F TD | CFM    | No. of<br>Fans | 208-230V/1           | 460V/1 |
|-----------|-------------|----------------------------------------|--------|----------------|----------------------|--------|
|           |             | R454A/R454C/R455A                      |        |                | Total Fan Motor Amps |        |
| 6 FPI     | RAH6A038*DA | 38,000                                 | 5,920  | 1              | 6.3                  | 3.1    |
|           | RAH6A053*DA | 53,000                                 | 5,870  | 1              | 6.3                  | 3.1    |
|           | RAH6A064*DA | 64,000                                 | 5,750  | 1              | 6.3                  | 3.1    |
|           | RAH6A076*DA | 76,000                                 | 11,850 | 2              | 12.6                 | 6.2    |
|           | RAH6A108*DA | 108,000                                | 11,730 | 2              | 12.6                 | 6.2    |
|           | RAH6A130*DA | 130,000                                | 11,500 | 2              | 12.6                 | 6.2    |
|           | RAH6A162*DA | 162,000                                | 17,600 | 3              | 18.9                 | 9.3    |
|           | RAH6A193*DA | 193,000                                | 17,250 | 3              | 18.9                 | 9.3    |
|           | RAH6A215*DA | 215,000                                | 23,460 | 4              | 25.2                 | 12.4   |
|           | RAH6A263*DA | 263,000                                | 23,000 | 4              | 25.2                 | 12.4   |

| Model No. |             | 208-230V/1 |      |                              |      | 460V/1     |      |                              |      |
|-----------|-------------|------------|------|------------------------------|------|------------|------|------------------------------|------|
|           |             | Base Model |      | EcoNet® Enabled <sup>1</sup> |      | Base Model |      | EcoNet® Enabled <sup>1</sup> |      |
|           |             | MCA        | MOPD | MCA                          | MOPD | MCA        | MOPD | MCA                          | MOPD |
| 6 FPI     | RAH6A038*DA | 15         | 20   | 15                           | 20   | 15         | 20   | 15                           | 20   |
|           | RAH6A053*DA | 15         | 20   | 15                           | 20   | 15         | 20   | 15                           | 20   |
|           | RAH6A064*DA | 15         | 20   | 15                           | 20   | 15         | 20   | 15                           | 20   |
|           | RAH6A076*DA | 15         | 20   | 16.2                         | 20   | 15         | 20   | 15                           | 20   |
|           | RAH6A108*DA | 15         | 20   | 16.2                         | 20   | 15         | 20   | 15                           | 20   |
|           | RAH6A130*DA | 15         | 20   | 16.2                         | 20   | 15         | 20   | 15                           | 20   |
|           | RAH6A162*DA | 20.5       | 25   | 22.5                         | 25   | 15         | 20   | 15                           | 20   |
|           | RAH6A193*DA | 20.5       | 25   | 22.5                         | 25   | 15         | 20   | 15                           | 20   |
|           | RAH6A215*DA | 26.8       | 30   | 28.8                         | 30   | 15         | 20   | 15                           | 20   |
|           | RAH6A263*DA | 26.8       | 30   | 28.8                         | 30   | 15         | 20   | 15                           | 20   |

\* Asterisk represents a variable character based on voltage ordered. See nomenclature on page 4 for details.

Dual Speed EC Motors are compliant with California Title 24 Regulations

<sup>1</sup> 208-230 ratings include 2 amp for controls on EcoNet® Enabled units. 460 ratings include 1 amp for controls on EcoNet® Enabled units.

APPLICATION RATING & ELECTRICAL DATA

MEDIUM TEMPERATURE ELECTRIC DEFROST // 6 FPI

| Model No. |             | BTUH Capacity<br>@ +25°F SST & 10°F TD | CFM    | No. of<br>Fans | 208-230V/1           | 460V/1 |
|-----------|-------------|----------------------------------------|--------|----------------|----------------------|--------|
|           |             | R454A/R454C/R455A                      |        |                | Total Fan Motor Amps |        |
| 6 FPI     | RAH6D037*DA | 38,000                                 | 5,920  | 1              | 6.3                  | 3.1    |
|           | RAH6D052*DA | 53,000                                 | 5,870  | 1              | 6.3                  | 3.1    |
|           | RAH6D063*DA | 64,000                                 | 5,750  | 1              | 6.3                  | 3.1    |
|           | RAH6D077*DA | 76,000                                 | 11,850 | 2              | 12.6                 | 6.2    |
|           | RAH6D107*DA | 108,000                                | 11,730 | 2              | 12.6                 | 6.2    |
|           | RAH6D129*DA | 130,000                                | 11,500 | 2              | 12.6                 | 6.2    |
|           | RAH6D161*DA | 162,000                                | 17,600 | 3              | 18.9                 | 9.3    |
|           | RAH6D192*DA | 193,000                                | 17,250 | 3              | 18.9                 | 9.3    |
|           | RAH6D214*DA | 215,000                                | 23,460 | 4              | 25.2                 | 12.4   |
|           | RAH6D262*DA | 263,000                                | 23,000 | 4              | 25.2                 | 12.4   |

\* Asterisk represents a variable character based on voltage ordered. See nomenclature on page 4 for details.

## APPLICATION RATING &amp; ELECTRICAL DATA

MEDIUM TEMPERATURE ELECTRIC DEFROST // 6 FPI

| Model No. |             | 208-230V/3 |      |                 |      |                 |                  |                   | Heater Watts |
|-----------|-------------|------------|------|-----------------|------|-----------------|------------------|-------------------|--------------|
|           |             | Base Model |      | EcoNet® Enabled |      | Heater Amps     |                  |                   |              |
|           |             | MCA        | MOPD | MCA             | MOPD | No. of Circuits | Amps per Circuit | Total Heater Amps |              |
| 6 FPI     | RAH6D037EDA | 15         | 20   | 20.1            | 25   | 1               | 14.5             | 14.5              | 6,000        |
|           | RAH6D052EDA | 15         | 20   | 20.1            | 25   | 1               | 14.5             | 14.5              | 6,000        |
|           | RAH6D063EDA | 15         | 20   | 20.1            | 25   | 1               | 14.5             | 14.5              | 6,000        |
|           | RAH6D077EDA | 15         | 20   | 38.1            | 40   | 1               | 28.9             | 28.9              | 12,000       |
|           | RAH6D107EDA | 15         | 20   | 38.1            | 40   | 1               | 28.9             | 28.9              | 12,000       |
|           | RAH6D129EDA | 15         | 20   | 38.1            | 40   | 1               | 28.9             | 28.9              | 12,000       |
|           | RAH6D161EDA | 20.5       | 25   | 56.2            | 60   | 1               | 43.4             | 43.4              | 18,000       |
|           | RAH6D192EDA | 20.5       | 25   | 56.2            | 60   | 1               | 43.4             | 43.4              | 18,000       |
|           | RAH6D214EDA | 26.8       | 30   | 74.3            | 80   | 2               | 28.9             | 57.8              | 24,000       |
|           | RAH6D262EDA | 26.8       | 30   | 74.3            | 80   | 2               | 28.9             | 57.8              | 24,000       |

208-230 ratings include 2 amp for controls on EcoNet® Enabled units.

| Model No. |             | 460V/3     |      |                 |      |                 |                  |                   | Heater Watts |
|-----------|-------------|------------|------|-----------------|------|-----------------|------------------|-------------------|--------------|
|           |             | Base Model |      | EcoNet® Enabled |      | Heater Amps     |                  |                   |              |
|           |             | MCA        | MOPD | MCA             | MOPD | No. of Circuits | Amps per Circuit | Total Heater Amps |              |
| 6 FPI     | RAH6D037GDA | 15         | 20   | 15              | 20   | 1               | 7.5              | 7.5               | 6,000        |
|           | RAH6D052GDA | 15         | 20   | 15              | 20   | 1               | 7.5              | 7.5               | 6,000        |
|           | RAH6D063GDA | 15         | 20   | 15              | 20   | 1               | 7.5              | 7.5               | 6,000        |
|           | RAH6D077GDA | 15         | 20   | 19.8            | 20   | 1               | 15.1             | 15.1              | 12,000       |
|           | RAH6D107GDA | 15         | 20   | 19.8            | 20   | 1               | 15.1             | 15.1              | 12,000       |
|           | RAH6D129GDA | 15         | 20   | 19.8            | 20   | 1               | 15.1             | 15.1              | 12,000       |
|           | RAH6D161GDA | 15         | 20   | 29.3            | 30   | 1               | 22.6             | 22.6              | 18,000       |
|           | RAH6D192GDA | 15         | 20   | 29.3            | 30   | 1               | 22.6             | 22.6              | 18,000       |
|           | RAH6D214GDA | 15         | 20   | 38.7            | 40   | 1               | 30.2             | 30.2              | 24,000       |
|           | RAH6D262GDA | 15         | 20   | 38.7            | 40   | 1               | 30.2             | 30.2              | 24,000       |

460 ratings include 1 amp for controls on EcoNet® Enabled units.

## APPLICATION RATING &amp; ELECTRICAL DATA

## LOW TEMPERATURE ELECTRIC DEFROST // 6 FPI

| Model No. |             | BTUH Capacity<br>@ -20°F SST & 10°F TD <sup>1</sup> | CFM    | No. of<br>Fans | 208-230V/1           | 460V/1 |
|-----------|-------------|-----------------------------------------------------|--------|----------------|----------------------|--------|
|           |             | R454A/R454C/R455A                                   |        |                | Total Fan Motor Amps |        |
| 6 FPI     | RAH6E040*DA | 40,000                                              | 5,920  | 1              | 6.3                  | 3.1    |
|           | RAH6E053*DA | 53,000                                              | 5,870  | 1              | 6.3                  | 3.1    |
|           | RAH6E065*DA | 65,000                                              | 5,750  | 1              | 6.3                  | 3.1    |
|           | RAH6E080*DA | 80,000                                              | 11,850 | 2              | 12.6                 | 6.2    |
|           | RAH6E106*DA | 106,000                                             | 11,730 | 2              | 12.6                 | 6.2    |
|           | RAH6E131*DA | 131,000                                             | 11,500 | 2              | 12.6                 | 6.2    |
|           | RAH6E160*DA | 160,000                                             | 17,600 | 3              | 18.9                 | 9.3    |
|           | RAH6E188*DA | 188,000                                             | 17,250 | 3              | 18.9                 | 9.3    |
|           | RAH6E237*DA | 237,000                                             | 23,000 | 4              | 25.2                 | 12.4   |

\* Asterisk represents a variable character based on voltage ordered. See page 4 for nomenclature.

## Capacity Correction for Low Temp Electric Defrost

| SST (Dew)             | 0°F   | -10°F  | -20°F | -30°F  | -40°F |
|-----------------------|-------|--------|-------|--------|-------|
| Multiply Capacity by: | 1.075 | 1.0375 | 1     | 0.9625 | 0.925 |

<sup>1</sup> Capacity values adjusted using the Correction Table for Electric Defrost Evaporators.

## APPLICATION RATING &amp; ELECTRICAL DATA

## LOW TEMPERATURE ELECTRIC DEFROST // 6 FPI

| Model No. |             | 208-230V/3 |      |                 |      |                 |                   |                   | Heater Watts |
|-----------|-------------|------------|------|-----------------|------|-----------------|-------------------|-------------------|--------------|
|           |             | Base Model |      | EcoNet® Enabled |      | Heater Amps     |                   |                   |              |
|           |             | MCA        | MOPD | MCA             | MOPD | No. of Circuits | Amps Each Circuit | Total Heater Amps |              |
| 6 FPI     | RAH6E040EDA | 15         | 20   | 20.1            | 25   | 1               | 14.5              | 14.5              | 6,000        |
|           | RAH6E053EDA | 15         | 20   | 20.1            | 25   | 1               | 14.5              | 14.5              | 6,000        |
|           | RAH6E065EDA | 15         | 20   | 20.1            | 25   | 1               | 14.5              | 14.5              | 6,000        |
|           | RAH6E080EDA | 15         | 20   | 38.1            | 40   | 1               | 28.9              | 28.9              | 12,000       |
|           | RAH6E106EDA | 15         | 20   | 38.1            | 40   | 1               | 28.9              | 28.9              | 12,000       |
|           | RAH6E131EDA | 15         | 20   | 38.1            | 40   | 1               | 28.9              | 28.9              | 12,000       |
|           | RAH6E160EDA | 20.5       | 25   | 56.2            | 60   | 1               | 43.4              | 43.4              | 18,000       |
|           | RAH6E188EDA | 20.5       | 25   | 56.2            | 60   | 1               | 43.4              | 43.4              | 18,000       |
|           | RAH6E237EDA | 26.8       | 30   | 74.3            | 80   | 2               | 28.9              | 57.8              | 24,000       |

208-230 ratings include 2 amp for controls on EcoNet® Enabled units.

| Model No. |             | 460V/3     |      |                 |      |                 |                   |                   | Heater Watts |
|-----------|-------------|------------|------|-----------------|------|-----------------|-------------------|-------------------|--------------|
|           |             | Base Model |      | EcoNet® Enabled |      | Heater Amps     |                   |                   |              |
|           |             | MCA        | MOPD | MCA             | MOPD | No. of Circuits | Amps Each Circuit | Total Heater Amps |              |
| 6 FPI     | RAH6E040GDA | 15         | 20   | 15              | 20   | 1               | 7.5               | 7.5               | 6,000        |
|           | RAH6E053GDA | 15         | 20   | 15              | 20   | 1               | 7.5               | 7.5               | 6,000        |
|           | RAH6E065GDA | 15         | 20   | 15              | 20   | 1               | 7.5               | 7.5               | 6,000        |
|           | RAH6E080GDA | 15         | 20   | 19.8            | 20   | 1               | 15.1              | 15.1              | 12,000       |
|           | RAH6E106GDA | 15         | 20   | 19.8            | 20   | 1               | 15.1              | 15.1              | 12,000       |
|           | RAH6E131GDA | 15         | 20   | 19.8            | 20   | 1               | 15.1              | 15.1              | 12,000       |
|           | RAH6E160GDA | 15         | 20   | 29.3            | 30   | 1               | 22.6              | 22.6              | 18,000       |
|           | RAH6E188GDA | 15         | 20   | 29.3            | 30   | 1               | 22.6              | 22.6              | 18,000       |
|           | RAH6E237GDA | 15         | 20   | 38.7            | 40   | 1               | 30.2              | 30.2              | 24,000       |

460 ratings include 1 amp for controls on EcoNet® Enabled units.

APPLICATION RATING & ELECTRICAL DATA

LOW TEMPERATURE ELECTRIC DEFROST // 4 FPI

| Model No. |             | BTUH Capacity<br>@ -20°F SST & 10°F TD <sup>1</sup> | CFM    | No. of<br>Fans | 208-230V/1           | 460V/1 |
|-----------|-------------|-----------------------------------------------------|--------|----------------|----------------------|--------|
|           |             | R454A/R454C/R455A                                   |        |                | Total Fan Motor Amps |        |
| 4 FPI     | RAH4E043*DA | 43,000                                              | 5,870  | 1              | 6.3                  | 3.1    |
|           | RAH4E053*DA | 53,000                                              | 5,750  | 1              | 6.3                  | 3.1    |
|           | RAH4E086*DA | 86,000                                              | 11,730 | 2              | 12.6                 | 6.2    |
|           | RAH4E105*DA | 105,000                                             | 11,500 | 2              | 12.6                 | 6.2    |
|           | RAH4E128*DA | 128,000                                             | 17,600 | 3              | 18.9                 | 9.3    |
|           | RAH4E158*DA | 158,000                                             | 17,250 | 3              | 18.9                 | 9.3    |
|           | RAH4E198*DA | 198,000                                             | 23,000 | 4              | 25.2                 | 12.4   |

\* Asterisk represents a variable character based on voltage ordered. See page 4 for nomenclature.

| Capacity Correction for Low Temp Electric Defrost |       |        |       |        |       |
|---------------------------------------------------|-------|--------|-------|--------|-------|
| SST (Dew)                                         | 0°F   | -10°F  | -20°F | -30°F  | -40°F |
| Multiply Capacity by:                             | 1.075 | 1.0375 | 1     | 0.9625 | 0.925 |

<sup>1</sup> Capacity values adjusted using the Correction Table for Electric Defrost Evaporators.

**APPLICATION RATING & ELECTRICAL DATA****LOW TEMPERATURE ELECTRIC DEFROST // 4 FPI**

| Model No. |             | 208-230V/3 |      |                 |      |                 |                   |                   | Heater Watts |
|-----------|-------------|------------|------|-----------------|------|-----------------|-------------------|-------------------|--------------|
|           |             | Base Model |      | EcoNet® Enabled |      | Heater Amps     |                   |                   |              |
|           |             | MCA        | MOPD | MCA             | MOPD | No. of Circuits | Amps Each Circuit | Total Heater Amps |              |
| 4 FPI     | RAH4E043EDA | 15         | 20   | 20.1            | 25   | 1               | 14.5              | 14.5              | 6,000        |
|           | RAH4E053EDA | 15         | 20   | 20.1            | 25   | 1               | 14.5              | 14.5              | 6,000        |
|           | RAH4E086EDA | 15         | 20   | 38.1            | 40   | 1               | 28.9              | 28.9              | 12,000       |
|           | RAH4E105EDA | 15         | 20   | 38.1            | 40   | 1               | 28.9              | 28.9              | 12,000       |
|           | RAH4E128EDA | 20.5       | 25   | 56.2            | 60   | 1               | 43.4              | 43.4              | 18,000       |
|           | RAH4E158EDA | 20.5       | 25   | 56.2            | 60   | 1               | 43.4              | 43.4              | 18,000       |
|           | RAH4E198EDA | 26.8       | 30   | 74.3            | 40   | 2               | 28.9              | 57.8              | 24,000       |

208-230 ratings include 2 amp for controls on EcoNet® Enabled units.

| Model No. |             | 460V/3     |      |                 |      |                 |                   |                   | Heater Watts |
|-----------|-------------|------------|------|-----------------|------|-----------------|-------------------|-------------------|--------------|
|           |             | Base Model |      | EcoNet® Enabled |      | Heater Amps     |                   |                   |              |
|           |             | MCA        | MOPD | MCA             | MOPD | No. of Circuits | Amps Each Circuit | Total Heater Amps |              |
| 4 FPI     | RAH4E043GDA | 15         | 20   | 15              | 20   | 1               | 7.5               | 7.5               | 6,000        |
|           | RAH4E053GDA | 15         | 20   | 15              | 20   | 1               | 7.5               | 7.5               | 6,000        |
|           | RAH4E086GDA | 15         | 20   | 19.8            | 20   | 1               | 15.1              | 15.1              | 12,000       |
|           | RAH4E105GDA | 15         | 20   | 19.8            | 20   | 1               | 15.1              | 15.1              | 12,000       |
|           | RAH4E128GDA | 15         | 20   | 29.3            | 30   | 1               | 22.6              | 22.6              | 18,000       |
|           | RAH4E158GDA | 15         | 20   | 29.3            | 30   | 1               | 22.6              | 22.6              | 18,000       |
|           | RAH4E198GDA | 15         | 20   | 38.7            | 40   | 1               | 30.2              | 30.2              | 24,000       |

460 ratings include 1 amp for controls on EcoNet® Enabled units.

## DISTRIBUTOR NOZZLES &amp; EXPANSION VALVES

AIR DEFROST // 6 FPI

| Model No.     |             | Nozzle @ Liq. Temp. |            | TXV @ Liq. Temp. |           | EEV @ Liq. Temp |        | No. of Circuits |
|---------------|-------------|---------------------|------------|------------------|-----------|-----------------|--------|-----------------|
|               |             | 50°F                | 100°F      | 50°F             | 100°F     | 50°F            | 100°F  |                 |
| 6 FPI - R454A | RAH6A038*DA | 1.5, TYPE G         | 4, TYPE G  | SBFTE-B-C        | SBFTE-C-C | SER-C           | SER-C  | 6               |
|               | RAH6A053*DA | 2, TYPE G           | 4, TYPE G  | SBFTE-C-C        | SBFTE-C-C | SER-C           | SER-C  | 6               |
|               | RAH6A064*DA | 3, TYPE G           | 6, TYPE G  | ERTE-4-C         | ERTE-6-C  | SER-C           | SER-C  | 12              |
|               | RAH6A076*DA | 3, TYPE G           | 8, TYPE G  | ERTE-5-C         | ERTE-8-C  | SER-C           | SER-D  | 12              |
|               | RAH6A108*DA | 5, TYPE C           | 10, TYPE C | ERTE-8-C         | ERTE-10-C | SER-D           | SER-D  | 18              |
|               | RAH6A130*DA | 5, TYPE C           | 15, TYPE E | ERTE-8-C         | ERTE-12-C | SER-D           | SER-D  | 24              |
|               | RAH6A162*DA | 8, TYPE A           | 17, TYPE A | OTE-15-C         | OTE-15-C  | SER-D           | SERI-F | 27              |
|               | RAH6A193*DA | 10, TYPE A          | 20, TYPE A | OTE-15-C         | OTE-20-C  | SER-D           | SERI-F | 36              |
|               | RAH6A215*DA | 12, TYPE A          | 20, TYPE A | OTE-15-C         | OTE-20-C  | SERI-F          | SERI-G | 27              |
|               | RAH6A263*DA | 15, TYPE A          | 30, TYPE A | OTE-20-C         | OTE-30-C  | SERI-F          | SERI-G | 36              |
| 6 FPI - R454C | RAH6A038*DA | 2, TYPE G           | 4, TYPE G  | SBFVE-B-C        | SBFVE-C-C | SER-C           | SER-C  | 6               |
|               | RAH6A053*DA | 2.5, TYPE G         | 5, TYPE G  | ERVE-4-C         | ERVE-6-C  | SER-C           | SER-C  | 6               |
|               | RAH6A064*DA | 3, TYPE G           | 6, TYPE G  | ERVE-5-C         | ERVE-8-C  | SER-C           | SER-D  | 12              |
|               | RAH6A076*DA | 4, TYPE G           | 8, TYPE G  | ERVE-6-C         | ERVE-20-C | SER-C           | SER-D  | 12              |
|               | RAH6A108*DA | 6, TYPE C           | 15, TYPE C | ERVE-10-C        | ERVE-12-C | SER-D           | SER-D  | 18              |
|               | RAH6A130*DA | 8, TYPE E           | 17, TYPE E | OVE-10-C         | OVE-15-C  | SER-D           | SERI-F | 24              |
|               | RAH6A162*DA | 10, TYPE A          | 20, TYPE A | OVE-15-C         | OVE-20-C  | SER-D           | SERI-F | 27              |
|               | RAH6A193*DA | 12, TYPE A          | 25, TYPE A | OVE-15-C         | OVE-20-C  | SERI-F          | SERI-G | 36              |
|               | RAH6A215*DA | 12, TYPE A          | 30, TYPE A | OVE-20-C         | OVE-30-C  | SERI-F          | SERI-G | 27              |
|               | RAH6A263*DA | 15, TYPE A          | 35, TYPE A | OVE-20-C         | OVE-30-C  | SERI-G          | SERI-J | 36              |
| 6 FPI - R455A | RAH6A038*DA | 2, TYPE G           | 4, TYPE G  | SBFVE-B-C        | SBF-C-C   | SER-C           | SER-C  | 6               |
|               | RAH6A053*DA | 3, TYPE G           | 5, TYPE G  | ERVE-4-C         | SBF-C-C   | SER-C           | SER-C  | 6               |
|               | RAH6A064*DA | 4, TYPE G           | 6, TYPE G  | ERVE-5-C         | ERVE-6-C  | SER-C           | SER-C  | 12              |
|               | RAH6A076*DA | 4, TYPE G           | 8, TYPE G  | ERVE-6-C         | ERVE-8-C  | SER-C           | SER-D  | 12              |
|               | RAH6A108*DA | 6, TYPE C           | 15, TYPE C | ERVE-10-C        | ERVE-10-C | SER-D           | SER-D  | 18              |
|               | RAH6A130*DA | 8, TYPE E           | 17, TYPE E | OVE-10-C         | ERVE-12-C | SER-D           | SER-D  | 24              |
|               | RAH6A162*DA | 12, TYPE A          | 20, TYPE A | OVE-15-C         | OVE-20-C  | SER-D           | SERI-F | 27              |
|               | RAH6A193*DA | 15, TYPE A          | 25, TYPE A | OVE-15-C         | OVE-20-C  | SERI-F          | SERI-F | 36              |
|               | RAH6A215*DA | 15, TYPE A          | 30, TYPE A | OVE-20-C         | OVE-20-C  | SERI-F          | SERI-G | 27              |
|               | RAH6A263*DA | 17, TYPE A          | 35, TYPE A | OVE-20-C         | OVE-30-C  | SERI-G          | SERI-G | 36              |

The Distributor lines are 1/4 diameter and 36 long.

\* Each asterisk represents a variable character based on voltage ordered. See nomenclature on page 4 for details.

Expansion valve selections based on +25° Suction Temp and 8°F to 12°F evaporator TD. Contact factory for operating conditions outside this range.

T Expansion valves are compatible with R454A refrigerant. V Expansion valves are compatible with R454C and R455A refrigerants.

For other valves, follow manufacturer's selection guidelines.

Base models (with no factory-mounted components) include nozzles sized for 100°F liquid, shipped loose.

**LOOSE COMPONENTS REQUIRED FOR A2L ISOLATION CONTROLS****A<sub>min</sub>** (MINIMUM ALLOWABLE ROOM SIZE) VALUES // AIR DEFROST // 6 FPI

| Model No.     |             | A <sub>min</sub> Values (Ft <sup>2</sup> ) |                |                |                |                | Loose SSOV Isolation Valve @ Liquid Temp |         |         | Loose CSOV Isolation CV |             |
|---------------|-------------|--------------------------------------------|----------------|----------------|----------------|----------------|------------------------------------------|---------|---------|-------------------------|-------------|
|               |             | 10 Ft Line Run                             | 20 Ft Line Run | 30 Ft Line Run | 40 Ft Line Run | 50 Ft Line Run | Size                                     | 50°F    | 100°F   | Size                    | Description |
| 6 FPI - R454A | RAH6A038*DA | 87                                         | 100            | 112            | 124            | 136            | 1/2                                      | SSOV-6  | SSOV-10 | 1-3/8                   | CSOV-11     |
|               | RAH6A053*DA | 123                                        | 141            | 159            | 178            | 196            | 5/8                                      | SSOV-10 | SSOV-10 | 1-3/8                   | CSOV-11     |
|               | RAH6A064*DA | 151                                        | 170            | 189            | 208            | 227            | 5/8                                      | SSOV-10 | SSOV-10 | 1-5/8                   | CSOV-13     |
|               | RAH6A076*DA | 151                                        | 170            | 189            | 208            | 227            | 5/8                                      | SSOV-10 | SSOV-10 | 1-5/8                   | CSOV-13     |
|               | RAH6A108*DA | 228                                        | 266            | 303            | 340            | 377            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|               | RAH6A130*DA | 281                                        | 319            | 356            | 393            | 430            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|               | RAH6A162*DA | 306                                        | 343            | 380            | 417            | 455            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|               | RAH6A193*DA | 387                                        | 426            | 466            | 505            | 544            | 7/8                                      | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
|               | RAH6A215*DA | 386                                        | 425            | 465            | 504            | 543            | 7/8                                      | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
|               | RAH6A263*DA | 514                                        | 577            | 639            | 702            | 764            | 1-1/8                                    | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
| 6 FPI - R454C | RAH6A038*DA | 84                                         | 96             | 108            | 119            | 131            | 1/2                                      | SSOV-6  | SSOV-10 | 1-3/8                   | CSOV-11     |
|               | RAH6A053*DA | 119                                        | 136            | 154            | 172            | 190            | 5/8                                      | SSOV-10 | SSOV-10 | 1-3/8                   | CSOV-11     |
|               | RAH6A064*DA | 146                                        | 165            | 183            | 201            | 220            | 5/8                                      | SSOV-10 | SSOV-10 | 1-5/8                   | CSOV-13     |
|               | RAH6A076*DA | 145                                        | 164            | 182            | 201            | 219            | 5/8                                      | SSOV-10 | SSOV-10 | 1-5/8                   | CSOV-13     |
|               | RAH6A108*DA | 221                                        | 257            | 293            | 329            | 365            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|               | RAH6A130*DA | 272                                        | 308            | 344            | 380            | 416            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|               | RAH6A162*DA | 296                                        | 332            | 368            | 404            | 440            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|               | RAH6A193*DA | 374                                        | 412            | 450            | 488            | 526            | 7/8                                      | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
|               | RAH6A215*DA | 373                                        | 411            | 449            | 487            | 525            | 7/8                                      | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
|               | RAH6A263*DA | 498                                        | 558            | 619            | 679            | 740            | 1-1/8                                    | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
| 6 FPI - R455A | RAH6A038*DA | 77                                         | 88             | 98             | 109            | 120            | 1/2                                      | SSOV-6  | SSOV-10 | 1-3/8                   | CSOV-11     |
|               | RAH6A053*DA | 108                                        | 124            | 141            | 157            | 173            | 5/8                                      | SSOV-10 | SSOV-10 | 1-3/8                   | CSOV-11     |
|               | RAH6A064*DA | 133                                        | 150            | 167            | 184            | 201            | 5/8                                      | SSOV-10 | SSOV-10 | 1-5/8                   | CSOV-13     |
|               | RAH6A076*DA | 133                                        | 150            | 166            | 183            | 200            | 5/8                                      | SSOV-10 | SSOV-10 | 1-5/8                   | CSOV-13     |
|               | RAH6A108*DA | 202                                        | 234            | 267            | 300            | 333            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|               | RAH6A130*DA | 248                                        | 281            | 314            | 347            | 380            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|               | RAH6A162*DA | 270                                        | 303            | 335            | 368            | 401            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|               | RAH6A193*DA | 341                                        | 376            | 411            | 445            | 480            | 7/8                                      | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
|               | RAH6A215*DA | 340                                        | 375            | 410            | 444            | 479            | 7/8                                      | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
|               | RAH6A263*DA | 454                                        | 509            | 564            | 620            | 675            | 1-1/8                                    | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |

Solenoid Shut Off Valves (SSOV) operate as double duty isolation/liquid line solenoid valve and are required to ship loose and be installed in the field, outside the refrigerated space.

SSOV/CSOV (Check Shut Off Valves) Selection Criteria: Maximum 10 Foot Line Rise, 100 Foot Line Run, 1:1 Condensing Unit/Evaporator.

Contact applications for additional lengths or design considerations.

A<sub>min</sub> values calculated using operating conditions included in UL 60335-2-89 101.DVU.1.2 and standard connection sizes (liquid and suction).

A<sub>min</sub> values provided for 10 Ft, 20 Ft, 30 Ft, 40 Ft and 50 Ft line lengths. Contact applications for additional lengths or design considerations.

A<sub>min</sub> values intended to determine compliance with UL 2-89 and is NOT for charging calculations.

## DISTRIBUTOR NOZZLES &amp; EXPANSION VALVES

MEDIUM TEMPERATURE ELECTRIC DEFROST // 6 FPI

| Model No.     |             | Nozzle @ Liq. Temp. |            | TXV @ Liq. Temp. |           | EEV @ Liq. Temp |        | No. of Circuits |
|---------------|-------------|---------------------|------------|------------------|-----------|-----------------|--------|-----------------|
|               |             | 50°F                | 100°F      | 50°F             | 100°F     | 50°F            | 100°F  |                 |
| 6 FPI - R454A | RAH6D037*DA | 1.5, TYPE G         | 4, TYPE G  | SBFTE-B-C        | SBFTE-C-C | SER-C           | SER-C  | 6               |
|               | RAH6D052*DA | 2, TYPE G           | 4, TYPE G  | SBFTE-C-C        | SBFTE-C-C | SER-C           | SER-C  | 6               |
|               | RAH6D063*DA | 3, TYPE G           | 6, TYPE G  | ERTE-4-C         | ERTE-6-C  | SER-C           | SER-C  | 12              |
|               | RAH6D077*DA | 3, TYPE G           | 8, TYPE G  | ERTE-5-C         | ERTE-8-C  | SER-C           | SER-D  | 12              |
|               | RAH6D107*DA | 5, TYPE C           | 10, TYPE C | ERTE-8-C         | ERTE-10-C | SER-D           | SER-D  | 18              |
|               | RAH6D129*DA | 5, TYPE C           | 15, TYPE E | ERTE-8-C         | ERTE-12-C | SER-D           | SER-D  | 24              |
|               | RAH6D161*DA | 8, TYPE A           | 17, TYPE A | OTE-15-C         | OTE-15-C  | SER-D           | SERI-F | 27              |
|               | RAH6D192*DA | 10, TYPE A          | 20, TYPE A | OTE-15-C         | OTE-20-C  | SER-D           | SERI-F | 36              |
|               | RAH6D214*DA | 12, TYPE A          | 20, TYPE A | OTE-15-C         | OTE-20-C  | SERI-F          | SERI-G | 27              |
|               | RAH6D262*DA | 15, TYPE A          | 30, TYPE A | OTE-20-C         | OTE-30-C  | SERI-F          | SERI-G | 36              |
| 6 FPI - R454C | RAH6D037*DA | 2, TYPE G           | 4, TYPE G  | SBFVE-B-C        | SBFVE-C-C | SER-C           | SER-C  | 6               |
|               | RAH6D052*DA | 2.5, TYPE G         | 5, TYPE G  | ERVE-4-C         | ERVE-6-C  | SER-C           | SER-C  | 6               |
|               | RAH6D063*DA | 3, TYPE G           | 6, TYPE G  | ERVE-5-C         | ERVE-8-C  | SER-C           | SER-D  | 12              |
|               | RAH6D077*DA | 4, TYPE G           | 8, TYPE G  | ERVE-6-C         | ERVE-20-C | SER-C           | SER-D  | 12              |
|               | RAH6D107*DA | 6, TYPE C           | 15, TYPE C | ERVE-10-C        | ERVE-12-C | SER-D           | SER-D  | 18              |
|               | RAH6D129*DA | 8, TYPE E           | 17, TYPE E | OVE-10-C         | OVE-15-C  | SER-D           | SERI-F | 24              |
|               | RAH6D161*DA | 10, TYPE A          | 20, TYPE A | OVE-15-C         | OVE-20-C  | SER-D           | SERI-F | 27              |
|               | RAH6D192*DA | 12, TYPE A          | 25, TYPE A | OVE-15-C         | OVE-20-C  | SERI-F          | SERI-G | 36              |
|               | RAH6D214*DA | 12, TYPE A          | 30, TYPE A | OVE-20-C         | OVE-30-C  | SERI-F          | SERI-G | 27              |
|               | RAH6D262*DA | 15, TYPE A          | 35, TYPE A | OVE-20-C         | OVE-30-C  | SERI-G          | SERI-J | 36              |
| 6 FPI - R455A | RAH6D037*DA | 2, TYPE G           | 4, TYPE G  | SBFVE-B-C        | SBF-C-C   | SER-C           | SER-C  | 6               |
|               | RAH6D052*DA | 3, TYPE G           | 5, TYPE G  | ERVE-4-C         | SBF-C-C   | SER-C           | SER-C  | 6               |
|               | RAH6D063*DA | 4, TYPE G           | 6, TYPE G  | ERVE-5-C         | ERVE-6-C  | SER-C           | SER-C  | 12              |
|               | RAH6D077*DA | 4, TYPE G           | 8, TYPE G  | ERVE-6-C         | ERVE-8-C  | SER-C           | SER-D  | 12              |
|               | RAH6D107*DA | 6, TYPE C           | 15, TYPE C | ERVE-10-C        | ERVE-10-C | SER-D           | SER-D  | 18              |
|               | RAH6D129*DA | 8, TYPE E           | 17, TYPE E | OVE-10-C         | ERVE-12-C | SER-D           | SER-D  | 24              |
|               | RAH6D161*DA | 12, TYPE A          | 20, TYPE A | OVE-15-C         | OVE-20-C  | SER-D           | SERI-F | 27              |
|               | RAH6D192*DA | 15, TYPE A          | 25, TYPE A | OVE-15-C         | OVE-20-C  | SERI-F          | SERI-F | 36              |
|               | RAH6D214*DA | 15, TYPE A          | 30, TYPE A | OVE-20-C         | OVE-20-C  | SERI-F          | SERI-G | 27              |
|               | RAH6D262*DA | 17, TYPE A          | 35, TYPE A | OVE-20-C         | OVE-30-C  | SERI-G          | SERI-G | 36              |

The Distributor lines are 1/4 diameter and 36 long.

\* Each asterisk represents a variable character based on voltage ordered. See nomenclature on page 4 for details.

Expansion valve selections based on +25° Suction Temp and 8°F to 12°F evaporator TD. Contact factory for operating conditions outside this range.

T Expansion valves are compatible with R454A refrigerant. V Expansion valves are compatible with R454C and R455A refrigerants.

For other valves, follow manufacturer's selection guidelines.

Base models (with no factory-mounted components) include nozzles sized for 100°F liquid, shipped loose.

**LOOSE COMPONENTS REQUIRED FOR A2L ISOLATION CONTROLS****A<sub>min</sub>** (MINIMUM ALLOWABLE ROOM SIZE) VALUES // MEDIUM TEMPERATURE ELECTRIC DEFROST // 6 FPI

| Model No.            |             | A <sub>min</sub> Values (Ft <sup>2</sup> ) |                |                |                |                | Loose SSOV Isolation Valve @ Liquid Temp |         |         | Loose CSOV Isolation CV |             |
|----------------------|-------------|--------------------------------------------|----------------|----------------|----------------|----------------|------------------------------------------|---------|---------|-------------------------|-------------|
|                      |             | 10 Ft Line Run                             | 20 Ft Line Run | 30 Ft Line Run | 40 Ft Line Run | 50 Ft Line Run | Size                                     | 50°F    | 100°F   | Size                    | Description |
| <b>6 FPI - R454A</b> | RAH6D037*DA | 87                                         | 100            | 112            | 124            | 136            | 1/2                                      | SSOV-6  | SSOV-10 | 1-3/8                   | CSOV-11     |
|                      | RAH6D052*DA | 123                                        | 141            | 159            | 178            | 196            | 5/8                                      | SSOV-10 | SSOV-10 | 1-3/8                   | CSOV-11     |
|                      | RAH6D063*DA | 151                                        | 170            | 189            | 208            | 227            | 5/8                                      | SSOV-10 | SSOV-10 | 1-5/8                   | CSOV-13     |
|                      | RAH6D077*DA | 151                                        | 170            | 189            | 208            | 227            | 5/8                                      | SSOV-10 | SSOV-10 | 1-5/8                   | CSOV-13     |
|                      | RAH6D107*DA | 228                                        | 266            | 303            | 340            | 377            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|                      | RAH6D129*DA | 281                                        | 319            | 356            | 393            | 430            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|                      | RAH6D161*DA | 306                                        | 343            | 380            | 417            | 455            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|                      | RAH6D192*DA | 387                                        | 426            | 466            | 505            | 544            | 7/8                                      | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
|                      | RAH6D214*DA | 386                                        | 425            | 465            | 504            | 543            | 7/8                                      | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
|                      | RAH6D262*DA | 514                                        | 577            | 639            | 702            | 764            | 1-1/8                                    | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
| <b>6 FPI - R454C</b> | RAH6D037*DA | 84                                         | 96             | 108            | 119            | 131            | 1/2                                      | SSOV-6  | SSOV-10 | 1-3/8                   | CSOV-11     |
|                      | RAH6D052*DA | 119                                        | 136            | 154            | 172            | 190            | 5/8                                      | SSOV-10 | SSOV-10 | 1-3/8                   | CSOV-11     |
|                      | RAH6D063*DA | 146                                        | 165            | 183            | 201            | 220            | 5/8                                      | SSOV-10 | SSOV-10 | 1-5/8                   | CSOV-13     |
|                      | RAH6D077*DA | 145                                        | 164            | 182            | 201            | 219            | 5/8                                      | SSOV-10 | SSOV-10 | 1-5/8                   | CSOV-13     |
|                      | RAH6D107*DA | 221                                        | 257            | 293            | 329            | 365            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|                      | RAH6D129*DA | 272                                        | 308            | 344            | 380            | 416            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|                      | RAH6D161*DA | 296                                        | 332            | 368            | 404            | 440            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|                      | RAH6D192*DA | 374                                        | 412            | 450            | 488            | 526            | 7/8                                      | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
|                      | RAH6D214*DA | 373                                        | 411            | 449            | 487            | 525            | 7/8                                      | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
|                      | RAH6D262*DA | 498                                        | 558            | 619            | 679            | 740            | 1-1/8                                    | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
| <b>6 FPI - R455A</b> | RAH6D037*DA | 77                                         | 88             | 98             | 109            | 120            | 1/2                                      | SSOV-6  | SSOV-10 | 1-3/8                   | CSOV-11     |
|                      | RAH6D052*DA | 108                                        | 124            | 141            | 157            | 173            | 5/8                                      | SSOV-10 | SSOV-10 | 1-3/8                   | CSOV-11     |
|                      | RAH6D063*DA | 133                                        | 150            | 167            | 184            | 201            | 5/8                                      | SSOV-10 | SSOV-10 | 1-5/8                   | CSOV-13     |
|                      | RAH6D077*DA | 133                                        | 150            | 166            | 183            | 200            | 5/8                                      | SSOV-10 | SSOV-10 | 1-5/8                   | CSOV-13     |
|                      | RAH6D107*DA | 202                                        | 234            | 267            | 300            | 333            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|                      | RAH6D129*DA | 248                                        | 281            | 314            | 347            | 380            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|                      | RAH6D161*DA | 270                                        | 303            | 335            | 368            | 401            | 7/8                                      | SSOV-19 | SSOV-19 | 2-1/8                   | CSOV-17     |
|                      | RAH6D192*DA | 341                                        | 376            | 411            | 445            | 480            | 7/8                                      | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
|                      | RAH6D214*DA | 340                                        | 375            | 410            | 444            | 479            | 7/8                                      | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
|                      | RAH6D262*DA | 454                                        | 509            | 564            | 620            | 675            | 1-1/8                                    | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |

Solenoid Shut Off Valves (SSOV) operate as double duty isolation/liquid line solenoid valve and are required to ship loose and be installed in the field, outside the refrigerated space.

SSOV/CSOV (Check Shut Off Valves) Selection Criteria: Maximum 10 Foot Line Rise, 100 Foot Line Run, 1:1 Condensing Unit/Evaporator.

Contact applications for additional lengths or design considerations.

A<sub>min</sub> values calculated using operating conditions included in UL 60335-2-89 101.DVU.1.2 and standard connection sizes (liquid and suction).

A<sub>min</sub> values provided for 10 Ft, 20 Ft, 30 Ft, 40 Ft and 50 Ft line lengths. Contact applications for additional lengths or design considerations.

A<sub>min</sub> values intended to determine compliance with UL 2-89 and is NOT for charging calculations.

## DISTRIBUTOR NOZZLES &amp; EXPANSION VALVES

LOW TEMPERATURE ELECTRIC DEFROST // 6 FPI

| Model No.     |             | Nozzle @ Liq. Temp. |            | TXV @ Liq. Temp. |          | EEV @ Liq. Temp |        | No. of Circuits |
|---------------|-------------|---------------------|------------|------------------|----------|-----------------|--------|-----------------|
|               |             | 50°F                | 100°F      | 50°F             | 100°F    | 50°F            | 100°F  |                 |
| 6 FPI - R454A | RAH6E040*DA | 3, TYPE E           | 6, TYPE E  | OTE-10-Z         | OTE-10-Z | SER-C           | SER-C  | 9               |
|               | RAH6E053*DA | 4, TYPE E           | 8, TYPE E  | OTE-10-Z         | OTE-10-Z | SER-C           | SER-C  | 9               |
|               | RAH6E065*DA | 5, TYPE C           | 12, TYPE C | OTE-10-Z         | OTE-15-Z | SER-C           | SER-C  | 18              |
|               | RAH6E080*DA | 8, TYPE C           | 15, TYPE C | OTE-10-Z         | OTE-15-Z | SER-C           | SER-D  | 18              |
|               | RAH6E106*DA | 12, TYPE A          | 20, TYPE A | OTE-15-Z         | OTE-20-Z | SER-C           | SER-D  | 27              |
|               | RAH6E131*DA | 15, TYPE A          | 25, TYPE A | OTE-20-Z         | OTE-30-Z | SER-D           | SER-D  | 36              |
|               | RAH6E160*DA | 17, TYPE A          | 25, TYPE A | OTE-20-Z         | OTE-30-Z | SER-D           | SERI-F | 27              |
|               | RAH6E188*DA | 20, TYPE A          | 35, TYPE A | OTE-30-Z         | OTE-40-Z | SER-D           | SERI-F | 36              |
|               | RAH6E237*DA | 25, TYPE A          | 40, TYPE A | OTE-30-Z         | OTE-40-Z | SERI-F          | SERI-G | 36              |
| 6 FPI - R454C | RAH6E040*DA | 4, TYPE E           | 8, TYPE E  | ERVE-5-Z         | ERVE-8-Z | SER-C           | SER-C  | 9               |
|               | RAH6E053*DA | 5, TYPE E           | 10, TYPE E | OVE-10-Z         | OVE-15-Z | SER-C           | SER-C  | 9               |
|               | RAH6E065*DA | 6, TYPE C           | 12, TYPE C | OVE-10-Z         | OVE-15-Z | SER-C           | SER-D  | 18              |
|               | RAH6E080*DA | 8, TYPE C           | 15, TYPE C | OVE-15-Z         | OVE-20-Z | SER-C           | SER-D  | 18              |
|               | RAH6E106*DA | 12, TYPE A          | 20, TYPE A | OVE-20-Z         | OVE-30-Z | SER-D           | SER-D  | 27              |
|               | RAH6E131*DA | 15, TYPE A          | 25, TYPE A | OVE-20-Z         | OVE-30-Z | SER-D           | SERI-F | 36              |
|               | RAH6E160*DA | 17, TYPE A          | 25, TYPE A | OVE-30-Z         | OVE-40-Z | SER-D           | SERI-F | 27              |
|               | RAH6E188*DA | 20, TYPE A          | 35, TYPE A | OVE-30-Z         | OVE-40-Z | SERI-F          | SERI-G | 36              |
|               | RAH6E237*DA | 25, TYPE A          | 40, TYPE A | OVE-40-Z         | OVE-55-Z | SERI-F          | SERI-J | 36              |
| 6 FPI - R455A | RAH6E040*DA | 4, TYPE E           | 8, TYPE E  | ERVE-5-Z         | ERVE-8-Z | SER-C           | SER-C  | 9               |
|               | RAH6E053*DA | 5, TYPE E           | 10, TYPE E | OVE-10-Z         | OVE-10-Z | SER-C           | SER-C  | 9               |
|               | RAH6E065*DA | 8, TYPE C           | 12, TYPE C | OVE-10-Z         | OVE-15-Z | SER-C           | SER-C  | 18              |
|               | RAH6E080*DA | 10, TYPE C          | 15, TYPE C | OVE-15-Z         | OVE-20-Z | SER-C           | SER-D  | 18              |
|               | RAH6E106*DA | 15, TYPE A          | 20, TYPE A | OVE-20-Z         | OVE-20-Z | SER-D           | SER-D  | 27              |
|               | RAH6E131*DA | 17, TYPE A          | 25, TYPE A | OVE-20-Z         | OVE-30-Z | SER-D           | SER-D  | 36              |
|               | RAH6E160*DA | 20, TYPE A          | 25, TYPE A | OVE-30-Z         | OVE-40-Z | SER-D           | SERI-F | 27              |
|               | RAH6E188*DA | 25, TYPE A          | 35, TYPE A | OVE-30-Z         | OVE-40-Z | SERI-F          | SERI-F | 36              |
|               | RAH6E237*DA | 30, TYPE A          | 40, TYPE A | OVE-40-Z         | OVE-40-Z | SERI-F          | SERI-G | 36              |

The Distributor lines are 1/4 diameter and 36 long.

\* Each asterisk represents a variable character based on voltage ordered. See nomenclature on page 4 for details.

Expansion valve selections based on +25° Suction Temp and 8°F to 12°F evaporator TD. Contact factory for operating conditions outside this range.

T Expansion valves are compatible with R454A refrigerant. V Expansion valves are compatible with R454C and R455A refrigerants.

For other valves, follow manufacturer's selection guidelines.

Base models (with no factory-mounted components) include nozzles sized for 100°F liquid, shipped loose.

**LOOSE COMPONENTS REQUIRED FOR A2L ISOLATION CONTROLS****A<sub>min</sub>** (MINIMUM ALLOWABLE ROOM SIZE) VALUES // LOW TEMPERATURE ELECTRIC DEFROST // 6 FPI

| Model No.            |             | A <sub>min</sub> Values (Ft <sup>2</sup> ) |                |                |                |                | Loose SSOV Isolation Valve @ Liquid Temp |         |         | Loose CSOV Isolation CV |             |
|----------------------|-------------|--------------------------------------------|----------------|----------------|----------------|----------------|------------------------------------------|---------|---------|-------------------------|-------------|
|                      |             | 10 Ft Line Run                             | 20 Ft Line Run | 30 Ft Line Run | 40 Ft Line Run | 50 Ft Line Run | Size                                     | 50°F    | 100°F   | Size                    | Description |
| <b>6 FPI - R454A</b> | RAH6E040*DA | 95                                         | 107            | 120            | 132            | 145            | 1/2                                      | SSOV-6  | SSOV-10 | 2-1/8                   | CSOV-17     |
|                      | RAH6E053*DA | 127                                        | 146            | 164            | 183            | 202            | 5/8                                      | SSOV-10 | SSOV-10 | 2-1/8                   | CSOV-17     |
|                      | RAH6E065*DA | 153                                        | 172            | 190            | 209            | 228            | 5/8                                      | SSOV-10 | SSOV-10 | 2-1/8                   | CSOV-17     |
|                      | RAH6E080*DA | 152                                        | 172            | 192            | 211            | 231            | 7/8                                      | SSOV-10 | SSOV-19 | 2-5/8                   | CSOV-21     |
|                      | RAH6E106*DA | 234                                        | 271            | 307            | 343            | 379            | 7/8                                      | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
|                      | RAH6E131*DA | 286                                        | 323            | 361            | 398            | 436            | 7/8                                      | SSOV-19 | SSOV-19 | 3-1/8                   | -           |
|                      | RAH6E160*DA | 310                                        | 348            | 385            | 423            | 460            | 7/8                                      | SSOV-19 | SSOV-19 | 3-1/8                   | -           |
|                      | RAH6E188*DA | 387                                        | 426            | 465            | 504            | 543            | 1-1/8                                    | SSOV-19 | SSOV-19 | 3-5/8                   | -           |
|                      | RAH6E237*DA | 485                                        | 524            | 563            | 602            | 641            | 1-1/8                                    | SSOV-19 | SSOV-19 | 3-5/8                   | -           |
| <b>6 FPI - R454C</b> | RAH6E040*DA | 92                                         | 104            | 116            | 128            | 128            | 1/2                                      | SSOV-6  | SSOV-10 | 2-1/8                   | CSOV-17     |
|                      | RAH6E053*DA | 123                                        | 141            | 159            | 177            | 177            | 5/8                                      | SSOV-10 | SSOV-10 | 2-1/8                   | CSOV-17     |
|                      | RAH6E065*DA | 148                                        | 166            | 184            | 203            | 203            | 5/8                                      | SSOV-10 | SSOV-10 | 2-1/8                   | CSOV-17     |
|                      | RAH6E080*DA | 148                                        | 167            | 186            | 205            | 205            | 7/8                                      | SSOV-10 | SSOV-19 | 2-5/8                   | CSOV-21     |
|                      | RAH6E106*DA | 228                                        | 263            | 298            | 333            | 333            | 7/8                                      | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
|                      | RAH6E131*DA | 277                                        | 313            | 350            | 386            | 386            | 7/8                                      | SSOV-19 | SSOV-19 | 3-1/8                   | -           |
|                      | RAH6E160*DA | 301                                        | 337            | 374            | 410            | 410            | 7/8                                      | SSOV-19 | SSOV-19 | 3-1/8                   | -           |
|                      | RAH6E188*DA | 376                                        | 413            | 451            | 488            | 488            | 1-1/8                                    | SSOV-19 | SSOV-19 | 3-5/8                   | -           |
|                      | RAH6E237*DA | 471                                        | 508            | 546            | 583            | 583            | 1-1/8                                    | SSOV-19 | SSOV-19 | 3-5/8                   | -           |
| <b>6 FPI - R455A</b> | RAH6E040*DA | 84                                         | 95             | 106            | 117            | 127            | 1/2                                      | SSOV-6  | SSOV-10 | 2-1/8                   | CSOV-17     |
|                      | RAH6E053*DA | 112                                        | 129            | 145            | 162            | 178            | 5/8                                      | SSOV-10 | SSOV-10 | 2-1/8                   | CSOV-17     |
|                      | RAH6E065*DA | 135                                        | 152            | 168            | 185            | 201            | 5/8                                      | SSOV-10 | SSOV-10 | 2-1/8                   | CSOV-17     |
|                      | RAH6E080*DA | 135                                        | 152            | 169            | 187            | 204            | 7/8                                      | SSOV-10 | SSOV-19 | 2-5/8                   | CSOV-21     |
|                      | RAH6E106*DA | 207                                        | 239            | 271            | 303            | 335            | 7/8                                      | SSOV-19 | SSOV-19 | 2-5/8                   | CSOV-21     |
|                      | RAH6E131*DA | 253                                        | 286            | 319            | 352            | 385            | 7/8                                      | SSOV-19 | SSOV-19 | 3-1/8                   | -           |
|                      | RAH6E160*DA | 275                                        | 308            | 341            | 374            | 407            | 7/8                                      | SSOV-19 | SSOV-19 | 3-1/8                   | -           |
|                      | RAH6E188*DA | 342                                        | 377            | 411            | 445            | 480            | 1-1/8                                    | SSOV-19 | SSOV-19 | 3-5/8                   | -           |
|                      | RAH6E237*DA | 429                                        | 463            | 498            | 532            | 566            | 1-1/8                                    | SSOV-19 | SSOV-19 | 3-5/8                   | -           |

Solenoid Shut Off Valves (SSOV) operate as double duty isolation/liquid line solenoid valve and are required to ship loose and be installed in the field, outside the refrigerated space.

SSOV/CSOV (Check Shut Off Valves) Selection Criteria: Maximum 10 Foot Line Rise, 100 Foot Line Run, 1:1 Condensing Unit/Evaporator.

Contact applications for additional lengths or design considerations.

A<sub>min</sub> values calculated using operating conditions included in UL 60335-2-89 101.DVU.1.2 and standard connection sizes (liquid and suction).

A<sub>min</sub> values provided for 10 Ft, 20 Ft, 30 Ft, 40 Ft and 50 Ft line lengths. Contact applications for additional lengths or design considerations.

A<sub>min</sub> values intended to determine compliance with UL 2-89 and is NOT for charging calculations.

## DISTRIBUTOR NOZZLES &amp; EXPANSION VALVES

LOW TEMPERATURE ELECTRIC DEFROST // 4 FPI

| Model No.     |             | Nozzle @ Liq. Temp. |            | TXV @ Liq. Temp. |          | EEV @ Liq. Temp |        | No. of Circuits |
|---------------|-------------|---------------------|------------|------------------|----------|-----------------|--------|-----------------|
|               |             | 50°F                | 100°F      | 50°F             | 100°F    | 50°F            | 100°F  |                 |
| 4 FPI - R454A | RAH4E043*DA | 4, TYPE E           | 6, TYPE E  | OTE-10-Z         | OTE-10-Z | SER-C           | SER-C  | 9               |
|               | RAH4E053*DA | 5, TYPE G           | 10, TYPE G | OTE-10-Z         | OTE-10-Z | SER-C           | SER-C  | 12              |
|               | RAH4E086*DA | 8, TYPE C           | 15, TYPE C | OTE-15-Z         | OTE-15-Z | SER-C           | SER-D  | 18              |
|               | RAH4E105*DA | 12, TYPE C          | 20, TYPE C | OTE-15-Z         | OTE-20-Z | SER-C           | SER-D  | 24              |
|               | RAH4E128*DA | 12, TYPE A          | 25, TYPE A | OTE-20-Z         | OTE-20-Z | SER-D           | SER-D  | 27              |
|               | RAH4E158*DA | 17, TYPE A          | 30, TYPE A | OTE-20-Z         | OTE-30-Z | SER-D           | SERI-F | 36              |
|               | RAH4E198*DA | 20, TYPE A          | 35, TYPE A | OTE-30-Z         | OTE-40-Z | SER-D           | SERI-F | 36              |
| 4 FPI - R454C | RAH4E043*DA | 4, TYPE E           | 8, TYPE E  | OVE-10-Z         | OVE-10-Z | SER-C           | SER-C  | 9               |
|               | RAH4E053*DA | 5, TYPE G           | 10, TYPE G | OVE-10-Z         | OVE-15-Z | SER-C           | SER-C  | 12              |
|               | RAH4E086*DA | 10, TYPE C          | 15, TYPE C | OVE-15-Z         | OVE-20-Z | SER-C           | SER-D  | 18              |
|               | RAH4E105*DA | 12, TYPE C          | 20, TYPE C | OVE-20-Z         | OVE-30-Z | SER-D           | SER-D  | 24              |
|               | RAH4E128*DA | 15, TYPE A          | 25, TYPE A | OVE-20-Z         | OVE-30-Z | SER-D           | SERI-F | 27              |
|               | RAH4E158*DA | 20, TYPE A          | 30, TYPE A | OVE-30-Z         | OVE-40-Z | SER-D           | SERI-F | 36              |
|               | RAH4E198*DA | 20, TYPE A          | 35, TYPE A | OVE-30-Z         | OVE-40-Z | SERI-F          | SERI-G | 36              |
| 4 FPI - R455A | RAH4E043*DA | 4, TYPE E           | 8, TYPE E  | OVE-10-Z         | ERVE-8-Z | SER-C           | SER-C  | 9               |
|               | RAH4E053*DA | 6, TYPE G           | 10, TYPE G | OVE-10-Z         | OVE-10-Z | SER-C           | SER-C  | 12              |
|               | RAH4E086*DA | 10, TYPE C          | 15, TYPE C | OVE-15-Z         | OVE-20-Z | SER-C           | SER-D  | 18              |
|               | RAH4E105*DA | 12, TYPE C          | 20, TYPE C | OVE-20-Z         | OVE-20-Z | SER-D           | SER-D  | 24              |
|               | RAH4E128*DA | 15, TYPE A          | 25, TYPE A | OVE-20-Z         | OVE-30-Z | SER-D           | SER-D  | 27              |
|               | RAH4E158*DA | 20, TYPE A          | 30, TYPE A | OVE-30-Z         | OVE-30-Z | SER-D           | SERI-F | 36              |
|               | RAH4E198*DA | 25, TYPE A          | 35, TYPE A | OVE-30-Z         | OVE-40-Z | SERI-F          | SERI-G | 36              |

The Distributor lines are 1/4 diameter and 36 long.

\* Each asterisk represents a variable character based on voltage ordered. See nomenclature on page 4 for details.

Expansion valve selections based on +25° Suction Temp and 8°F to 12°F evaporator TD. Contact factory for operating conditions outside this range.

T Expansion valves are compatible with R454A refrigerant. V Expansion valves are compatible with R454C and R455A refrigerants.

For other valves, follow manufacturer's selection guidelines.

Base models (with no factory-mounted components) include nozzles sized for 100°F liquid, shipped loose.

**LOOSE COMPONENTS REQUIRED FOR A2L ISOLATION CONTROLS****A<sub>min</sub>** (MINIMUM ALLOWABLE ROOM SIZE) VALUES // LOW TEMPERATURE ELECTRIC DEFROST // 4 FPI

| Model No.     |             | A <sub>min</sub> Values (Ft <sup>2</sup> ) |                   |                   |                   |                   | Loose SSOV Isolation Valve<br>@ Liquid Temp |         |         | Loose CSOV<br>Isolation CV |             |
|---------------|-------------|--------------------------------------------|-------------------|-------------------|-------------------|-------------------|---------------------------------------------|---------|---------|----------------------------|-------------|
|               |             | 10 Ft<br>Line Run                          | 20 Ft<br>Line Run | 30 Ft<br>Line Run | 40 Ft<br>Line Run | 50 Ft<br>Line Run | Size                                        | 50°F    | 100°F   | Size                       | Description |
| 4 FPI - R454A | RAH4E043*DA | 127                                        | 146               | 164               | 183               | 202               | 5/8                                         | SSOV-6  | SSOV-10 | 2-1/8                      | CSOV-17     |
|               | RAH4E053*DA | 153                                        | 172               | 190               | 209               | 228               | 5/8                                         | SSOV-10 | SSOV-10 | 2-1/8                      | CSOV-17     |
|               | RAH4E086*DA | 202                                        | 222               | 242               | 261               | 281               | 7/8                                         | SSOV-10 | SSOV-19 | 2-5/8                      | CSOV-21     |
|               | RAH4E105*DA | 284                                        | 321               | 357               | 393               | 429               | 7/8                                         | SSOV-19 | SSOV-19 | 2-5/8                      | CSOV-21     |
|               | RAH4E128*DA | 310                                        | 348               | 385               | 423               | 460               | 7/8                                         | SSOV-19 | SSOV-19 | 3-1/8                      | -           |
|               | RAH4E158*DA | 386                                        | 423               | 461               | 498               | 536               | 7/8                                         | SSOV-19 | SSOV-19 | 3-1/8                      | -           |
|               | RAH4E198*DA | 485                                        | 524               | 563               | 602               | 641               | 1-1/8                                       | SSOV-19 | SSOV-19 | 3-5/8                      | -           |
| 4 FPI - R454C | RAH4E043*DA | 123                                        | 141               | 159               | 177               | 195               | 5/8                                         | SSOV-6  | SSOV-10 | 2-1/8                      | CSOV-17     |
|               | RAH4E053*DA | 148                                        | 166               | 184               | 203               | 221               | 5/8                                         | SSOV-10 | SSOV-10 | 2-1/8                      | CSOV-17     |
|               | RAH4E086*DA | 196                                        | 215               | 234               | 253               | 272               | 7/8                                         | SSOV-10 | SSOV-19 | 2-5/8                      | CSOV-21     |
|               | RAH4E105*DA | 276                                        | 311               | 346               | 381               | 416               | 7/8                                         | SSOV-19 | SSOV-19 | 2-5/8                      | CSOV-21     |
|               | RAH4E128*DA | 301                                        | 337               | 374               | 410               | 446               | 7/8                                         | SSOV-19 | SSOV-19 | 3-1/8                      | -           |
|               | RAH4E158*DA | 375                                        | 411               | 447               | 483               | 519               | 7/8                                         | SSOV-19 | SSOV-19 | 3-1/8                      | -           |
|               | RAH4E198*DA | 471                                        | 508               | 546               | 583               | 621               | 1-1/8                                       | SSOV-19 | SSOV-19 | 3-5/8                      | -           |
| 4 FPI - R455A | RAH4E043*DA | 112                                        | 129               | 145               | 162               | 178               | 5/8                                         | SSOV-6  | SSOV-10 | 2-1/8                      | CSOV-17     |
|               | RAH4E053*DA | 135                                        | 152               | 168               | 185               | 201               | 5/8                                         | SSOV-10 | SSOV-10 | 2-1/8                      | CSOV-17     |
|               | RAH4E086*DA | 179                                        | 196               | 213               | 231               | 248               | 7/8                                         | SSOV-10 | SSOV-19 | 2-5/8                      | CSOV-21     |
|               | RAH4E105*DA | 252                                        | 284               | 316               | 348               | 380               | 7/8                                         | SSOV-19 | SSOV-19 | 2-5/8                      | CSOV-21     |
|               | RAH4E128*DA | 275                                        | 308               | 341               | 374               | 407               | 7/8                                         | SSOV-19 | SSOV-19 | 3-1/8                      | -           |
|               | RAH4E158*DA | 341                                        | 374               | 407               | 440               | 473               | 7/8                                         | SSOV-19 | SSOV-19 | 3-1/8                      | -           |
|               | RAH4E198*DA | 429                                        | 463               | 498               | 532               | 566               | 1-1/8                                       | SSOV-19 | SSOV-19 | 3-5/8                      | -           |

Solenoid Shut Off Valves (SSOV) operate as double duty isolation/liquid line solenoid valve and are required to ship loose and be installed in the field, outside the refrigerated space.

SSOV/CSOV (Check Shut Off Valves) Selection Criteria: Maximum 10 Foot Line Rise, 100 Foot Line Run, 1:1 Condensing Unit/Evaporator.

Contact applications for additional lengths or design considerations.

A<sub>min</sub> values calculated using operating conditions included in UL 60335-2-89 101.DVU.1.2 and standard connection sizes (liquid and suction).

A<sub>min</sub> values provided for 10 Ft, 20 Ft, 30 Ft, 40 Ft and 50 Ft line lengths. Contact applications for additional lengths or design considerations.

A<sub>min</sub> values intended to determine compliance with UL 2-89 and is NOT for charging calculations.

## PHYSICAL SPECIFICATIONS

### AIR DEFROST

| Model No. |             | Fan<br>Diam.<br>(In.) | Motor Data    |     |     | Refrigerant<br>Connections (In.) |         | No. of<br>Hangers<br>Slot<br>Location | Fig. | Unit Dimensions (In.) |        |        | Approx.<br>Unit Wt.<br>(Lbs.) |
|-----------|-------------|-----------------------|---------------|-----|-----|----------------------------------|---------|---------------------------------------|------|-----------------------|--------|--------|-------------------------------|
|           |             |                       | Motor<br>Qty. | HP  | RPM | Liquid<br>Line <sup>^</sup>      | Suction |                                       |      | L                     | W      | H      |                               |
| 6 FRI     | RAH6A038*DA | 30                    | 1             | 3/4 | 850 | 1/2                              | 1-3/8   | 4                                     | 1    | 59-7/8                | 27-3/8 | 49-1/4 | 293                           |
|           | RAH6A053*DA | 30                    | 1             | 3/4 | 850 | 5/8                              | 1-3/8   | 4                                     | 1    | 59-7/8                | 27-3/8 | 49-1/4 | 293                           |
|           | RAH6A064*DA | 30                    | 1             | 3/4 | 850 | 5/8                              | 1-5/8   | 4                                     | 1    | 59-7/8                | 27-3/8 | 49-1/4 | 293                           |
|           | RAH6A076*DA | 30                    | 2             | 3/4 | 850 | 5/8                              | 1-5/8   | 6                                     | 2    | 99-7/8                | 27-3/8 | 49-1/4 | 489                           |
|           | RAH6A108*DA | 30                    | 2             | 3/4 | 850 | 7/8                              | 2-1/8   | 6                                     | 2    | 99-7/8                | 27-3/8 | 49-1/4 | 489                           |
|           | RAH6A130*DA | 30                    | 2             | 3/4 | 850 | 7/8                              | 2-1/8   | 6                                     | 2    | 99-7/8                | 27-3/8 | 49-1/4 | 489                           |
|           | RAH6A162*DA | 30                    | 3             | 3/4 | 850 | 7/8                              | 2-1/8   | 8                                     | 3    | 139-7/8               | 27-3/8 | 49-1/4 | 652                           |
|           | RAH6A193*DA | 30                    | 3             | 3/4 | 850 | 7/8                              | 2-5/8   | 8                                     | 3    | 139-7/8               | 27-3/8 | 49-1/4 | 652                           |
|           | RAH6A215*DA | 30                    | 4             | 3/4 | 850 | 7/8                              | 2-5/8   | 10                                    | 4    | 179-7/8               | 27-3/8 | 49-1/4 | 837                           |
|           | RAH6A263*DA | 30                    | 4             | 3/4 | 850 | 1-1/8                            | 2-5/8   | 10                                    | 4    | 179-7/8               | 27-3/8 | 49-1/4 | 837                           |

### MEDIUM TEMPERATURE ELECTRIC DEFROST

| Model No. |             | Fan<br>Diam.<br>(In.) | Motor Data    |     |     | Refrigerant<br>Connections (In.) |         | No. of<br>Hangers<br>Slot<br>Location | Fig. | Unit Dimensions (In.) |        |        | Approx.<br>Unit Wt.<br>(Lbs.) |
|-----------|-------------|-----------------------|---------------|-----|-----|----------------------------------|---------|---------------------------------------|------|-----------------------|--------|--------|-------------------------------|
|           |             |                       | Motor<br>Qty. | HP  | RPM | Liquid<br>Line <sup>^</sup>      | Suction |                                       |      | L                     | W      | H      |                               |
| 6 FRI     | RAH6D037*DA | 30                    | 1             | 3/4 | 850 | 1/2                              | 1-3/8   | 4                                     | 1    | 59-7/8                | 27-3/8 | 49-1/4 | 293                           |
|           | RAH6D052*DA | 30                    | 1             | 3/4 | 850 | 5/8                              | 1-3/8   | 4                                     | 1    | 59-7/8                | 27-3/8 | 49-1/4 | 293                           |
|           | RAH6D063*DA | 30                    | 1             | 3/4 | 850 | 5/8                              | 1-5/8   | 4                                     | 1    | 59-7/8                | 27-3/8 | 49-1/4 | 293                           |
|           | RAH6D077*DA | 30                    | 2             | 3/4 | 850 | 5/8                              | 1-5/8   | 6                                     | 2    | 99-7/8                | 27-3/8 | 49-1/4 | 489                           |
|           | RAH6D107*DA | 30                    | 2             | 3/4 | 850 | 7/8                              | 2-1/8   | 6                                     | 2    | 99-7/8                | 27-3/8 | 49-1/4 | 489                           |
|           | RAH6D129*DA | 30                    | 2             | 3/4 | 850 | 7/8                              | 2-1/8   | 6                                     | 2    | 99-7/8                | 27-3/8 | 49-1/4 | 489                           |
|           | RAH6D161*DA | 30                    | 3             | 3/4 | 850 | 7/8                              | 2-1/8   | 8                                     | 3    | 139-7/8               | 27-3/8 | 49-1/4 | 652                           |
|           | RAH6D192*DA | 30                    | 3             | 3/4 | 850 | 7/8                              | 2-5/8   | 8                                     | 3    | 139-7/8               | 27-3/8 | 49-1/4 | 652                           |
|           | RAH6D214*DA | 30                    | 4             | 3/4 | 850 | 7/8                              | 2-5/8   | 10                                    | 4    | 179-7/8               | 27-3/8 | 49-1/4 | 837                           |
|           | RAH6D262*DA | 30                    | 4             | 3/4 | 850 | 1-1/8                            | 2-5/8   | 10                                    | 4    | 179-7/8               | 27-3/8 | 49-1/4 | 837                           |

\* Asterisk represents a variable character based on voltage ordered. See nomenclature on page 4 for details.

<sup>^</sup> For units with mounted TXV components. See Nozzle/TXV table for distributor connection size when TXV is field installed.

For dimensional distance between hanger slots, consult model's corresponding dimensional drawing. Hanger slots are 3/8 deep x 1 wide.

Drain connection is 1-1/4 NPT for all models.

For shipping dimensions and weights, see the Shipping information on pages 20-23 included with each dimensional drawing.

**PHYSICAL SPECIFICATIONS****LOW TEMPERATURE ELECTRIC DEFROST**

| Model No.    |             | Fan<br>Diam.<br>(In.) | Motor Data    |     |     | Refrigerant<br>Connections (In.) |         | No. of<br>Hangers<br>Slot<br>Location | Fig. | Unit Dimensions (In.) |        |        | Approx.<br>Unit Wt.<br>(Lbs.) |
|--------------|-------------|-----------------------|---------------|-----|-----|----------------------------------|---------|---------------------------------------|------|-----------------------|--------|--------|-------------------------------|
|              |             |                       | Motor<br>Qty. | HP  | RPM | Liquid<br>Line <sup>^</sup>      | Suction |                                       |      | L                     | W      | H      |                               |
| <b>6 FPI</b> | RAH6E040*DA | 30                    | 1             | 3/4 | 850 | 1/2                              | 2-1/8   | 4                                     | 1    | 59-7/8                | 27-3/8 | 49-1/4 | 293                           |
|              | RAH6E053*DA | 30                    | 1             | 3/4 | 850 | 5/8                              | 2-1/8   | 4                                     | 1    | 59-7/8                | 27-3/8 | 49-1/4 | 293                           |
|              | RAH6E065*DA | 30                    | 1             | 3/4 | 850 | 5/8                              | 2-1/8   | 4                                     | 1    | 59-7/8                | 27-3/8 | 49-1/4 | 293                           |
|              | RAH6E080*DA | 30                    | 2             | 3/4 | 850 | 7/8                              | 2-5/8   | 6                                     | 2    | 99-7/8                | 27-3/8 | 49-1/4 | 489                           |
|              | RAH6E106*DA | 30                    | 2             | 3/4 | 850 | 7/8                              | 2-5/8   | 6                                     | 2    | 99-7/8                | 27-3/8 | 49-1/4 | 489                           |
|              | RAH6E131*DA | 30                    | 2             | 3/4 | 850 | 7/8                              | 3-1/8   | 6                                     | 2    | 99-7/8                | 27-3/8 | 49-1/4 | 489                           |
|              | RAH6E160*DA | 30                    | 3             | 3/4 | 850 | 7/8                              | 3-1/8   | 8                                     | 3    | 139-7/8               | 27-3/8 | 49-1/4 | 652                           |
|              | RAH6E188*DA | 30                    | 3             | 3/4 | 850 | 1-1/8                            | 3-5/8   | 8                                     | 3    | 139-7/8               | 27-3/8 | 49-1/4 | 652                           |
|              | RAH6E237*DA | 30                    | 4             | 3/4 | 850 | 1-1/8                            | 3-5/8   | 10                                    | 4    | 179-7/8               | 27-3/8 | 49-1/4 | 837                           |
| <b>4 FPI</b> | RAH4E043*DA | 30                    | 1             | 3/4 | 850 | 5/8                              | 2-1/8   | 4                                     | 1    | 59-7/8                | 27-3/8 | 49-1/4 | 293                           |
|              | RAH4E053*DA | 30                    | 1             | 3/4 | 850 | 5/8                              | 2-1/8   | 4                                     | 1    | 59-7/8                | 27-3/8 | 49-1/4 | 293                           |
|              | RAH4E086*DA | 30                    | 2             | 3/4 | 850 | 7/8                              | 2-5/8   | 6                                     | 2    | 99-7/8                | 27-3/8 | 49-1/4 | 489                           |
|              | RAH4E105*DA | 30                    | 2             | 3/4 | 850 | 7/8                              | 2-5/8   | 6                                     | 2    | 99-7/8                | 27-3/8 | 49-1/4 | 489                           |
|              | RAH4E128*DA | 30                    | 3             | 3/4 | 850 | 7/8                              | 3-1/8   | 8                                     | 3    | 139-7/8               | 27-3/8 | 49-1/4 | 652                           |
|              | RAH4E158*DA | 30                    | 3             | 3/4 | 850 | 7/8                              | 3-1/8   | 8                                     | 3    | 139-7/8               | 27-3/8 | 49-1/4 | 652                           |
|              | RAH4E198*DA | 30                    | 4             | 3/4 | 850 | 1-1/8                            | 3-5/8   | 10                                    | 4    | 179-7/8               | 27-3/8 | 49-1/4 | 837                           |

\* Asterisk represents a variable character based on voltage ordered. See nomenclature on page 4 for details.

<sup>^</sup> For units with mounted TXV components. See Nozzle/TXV table for distributor connection size when TXV is field installed.

For dimensional distance between hanger slots, consult model's corresponding dimensional drawing. Hanger slots are 3/8 deep x 1 wide.


Drain connection is 1-1/4 NPT for all models.

For shipping dimensions and weights, see the Shipping information on pages 20-23 included with each dimensional drawing.


DIMENSIONAL DRAWINGS

Figure 1: Single Fan

Front View



Side View



Top View




FIGURE 1: SHIPPING INFORMATION


| No. of Fans | Shipping Dimensions (In.) |    |    | Shipping Weight (Lbs) |
|-------------|---------------------------|----|----|-----------------------|
|             | L                         | W  | H  |                       |
| 1           | 69                        | 42 | 66 | 470                   |

All mounting holes are 1/2 diameter.  
Mounted hanger spacers aid in the correct installation.  
All dimensions are in inches.


## DIMENSIONAL DRAWINGS

**Figure 2: Two Fan**


Front View



Side View



Top View



**FIGURE 2: SHIPPING INFORMATION**


| No. of Fans | Shipping Dimensions (In.) |    |    | Shipping Weight (Lbs) |
|-------------|---------------------------|----|----|-----------------------|
|             | L                         | W  | H  |                       |
| 2           | 109                       | 42 | 66 | 730                   |

All mounting holes are  $\frac{1}{2}$  diameter.  
 Mounted hanger spacers aid in the correct installation.  
 All dimensions are in inches.


DIMENSIONAL DRAWINGS

Figure 3: Three Fan

Front View



Side View



Top View




FIGURE 3: SHIPPING INFORMATION


| No. of Fans | Shipping Dimensions (In.) |    |    | Shipping Weight (Lbs) |
|-------------|---------------------------|----|----|-----------------------|
|             | L                         | W  | H  |                       |
| 3           | 146                       | 42 | 66 | 1,000                 |

All mounting holes are 1/2 diameter.  
Mounted hanger spacers aid in the correct installation.  
All dimensions are in inches.


## DIMENSIONAL DRAWINGS

Figure 4: Four Fan

### Front View



### Side View



### Top View




FIGURE 4: SHIPPING INFORMATION

| No. of Fans | Shipping Dimensions (In.) |    |    | Shipping Weight (Lbs) |
|-------------|---------------------------|----|----|-----------------------|
|             | L                         | W  | H  |                       |
| 4           | 189                       | 42 | 66 | 1,130                 |

All mounting holes are 1/2 diameter.  
Mounted hanger spacers aid in the correct installation.  
All dimensions are in inches.

## EVAPORATOR APPLICATION RATINGS

Multiple conditions combine to determine the application capacity of an evaporator. Walk-in space temperature, relative humidity, saturated suction temperature difference, and outdoor ambient temperature. All of the factors are considered when calculating an evaporator application rating. These ratings are considerably higher than the net capacity value used for DOE ratings (AWEF).

The AWEF of an evaporator is calculated using the dry coil capacity and the daily evaporator power consumption. Power consumption included fan and defrost power. Evaporator net capacity reported to the DOE database is dry coil capacity less the full power fan watts. DOE test conditions are at 10°F evaporator/SST temperature difference and less than 50% relative humidity and 96°F liquid temperature. These conditions create a uniform test method, but should not be used for equipment selection. The equipment selected would be too large for the application.

Published application ratings are a guideline for proper equipment selection. They account for true operating conditions experienced by equipment.

## AWEF RATING // COOLER & FREEZER MODELS

Department of Energy Annual  
Walk-In Energy Factor (AWEF) Ratings

| Cooler Models <sup>1</sup> |                              |     |      |
|----------------------------|------------------------------|-----|------|
| Base Model No.             | Defrost Type                 | FPI | AWEF |
| RAH6A038*DA                | Air Defrost                  | 6   | 9    |
| RAH6A053*DA                | Air Defrost                  | 6   | 9    |
| RAH6A064*DA                | Air Defrost                  | 6   | 9    |
| RAH6A076*DA                | Air Defrost                  | 6   | 9    |
| RAH6A108*DA                | Air Defrost                  | 6   | 9    |
| RAH6A130*DA                | Air Defrost                  | 6   | 9    |
| RAH6A162*DA                | Air Defrost                  | 6   | 9    |
| RAH6A193*DA                | Air Defrost                  | 6   | 9    |
| RAH6A215*DA                | Air Defrost                  | 6   | 9    |
| RAH6A263*DA                | Air Defrost                  | 6   | 9    |
| RAH6D037*DA                | Medium Temp Electric Defrost | 6   | 9    |
| RAH6D052*DA                | Medium Temp Electric Defrost | 6   | 9    |
| RAH6D063*DA                | Medium Temp Electric Defrost | 6   | 9    |
| RAH6D077*DA                | Medium Temp Electric Defrost | 6   | 9    |
| RAH6D107*DA                | Medium Temp Electric Defrost | 6   | 9    |
| RAH6D129*DA                | Medium Temp Electric Defrost | 6   | 9    |
| RAH6D161*DA                | Medium Temp Electric Defrost | 6   | 9    |
| RAH6D192*DA                | Medium Temp Electric Defrost | 6   | 9    |
| RAH6D214*DA                | Medium Temp Electric Defrost | 6   | 9    |
| RAH6D262*DA                | Medium Temp Electric Defrost | 6   | 9    |

\* Each asterisk represents a variable character based on defrost and voltage ordered. See page 4 for nomenclature.

Department of Energy Annual  
Walk-In Energy Factor (AWEF) Ratings

| Freezer Models <sup>2</sup> |                           |     |      |
|-----------------------------|---------------------------|-----|------|
| Base Model No.              | Defrost Type              | FPI | AWEF |
| RAH6E033*DA                 | Low Temp Electric Defrost | 6   | 4.15 |
| RAH6E044*DA                 | Low Temp Electric Defrost | 6   | 4.15 |
| RAH6E053*DA                 | Low Temp Electric Defrost | 6   | 4.15 |
| RAH6E066*DA                 | Low Temp Electric Defrost | 6   | 4.15 |
| RAH6E089*DA                 | Low Temp Electric Defrost | 6   | 4.15 |
| RAH6E109*DA                 | Low Temp Electric Defrost | 6   | 4.15 |
| RAH6E134*DA                 | Low Temp Electric Defrost | 6   | 4.15 |
| RAH6E163*DA                 | Low Temp Electric Defrost | 6   | 4.15 |
| RAH6E199*DA                 | Low Temp Electric Defrost | 6   | 4.15 |
| RAH4E035*DA                 | Low Temp Electric Defrost | 4   | 4.15 |
| RAH4E044*DA                 | Low Temp Electric Defrost | 4   | 4.15 |
| RAH4E071*DA                 | Low Temp Electric Defrost | 4   | 4.15 |
| RAH4E087*DA                 | Low Temp Electric Defrost | 4   | 4.15 |
| RAH4E107*DA                 | Low Temp Electric Defrost | 4   | 4.15 |
| RAH4E131*DA                 | Low Temp Electric Defrost | 4   | 4.15 |
| RAH4E167*DA                 | Low Temp Electric Defrost | 4   | 4.15 |

<sup>1</sup> If the model has a numerical value in the AWEF table below, the following statement applies:

The refrigeration system is designed and certified for use in walk-in cooler applications less than 3,000 sq. ft.

<sup>2</sup> If the model has a numerical value in the AWEF table below, the following statement applies:

The refrigeration system is designed and certified for use in walk-in cooler applications less than 3,000 sq. ft.





***Russell***

ENGINEERED FOR COOL.™

©2025 Heat Transfer Products Group

Published August 2025

RU-RHX-A2L-0825

**[russell.htpg.com](http://russell.htpg.com)**

This information is the most current and accurate information available and is subject to change without notice. HTPG makes no warranty or guarantee of any kind, express or implied, regarding the information set forth herein, including without limitation warranty regarding its currency, accuracy or completeness or any warranty of merchantability or fitness for a particular purpose.

